



CONTAIN-IT Plus Ball valve type 546 Pro PP-H/PE100 Connections for socket fusion

Model:

- Ball valve PP-H with spigots PE
- Manual operated
- Manual override with ratchet setting
- Pneumatic or electric actuator available separately
- Protective housing PVC-U PN6 / sealing according to inner pipe
- For easy installation and removal

d (mm)	D (mm)	PN (bar)	PN (Outer Pipe) (bar)	SDR	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
20	50	10	6	11	733 239 156	4.500	733 239 176	4.500
25	50	10	6	11	733 239 157	7.000	733 239 177	7.000
32	63	10	6	11	733 239 158	7.300	733 239 178	7.300
40	75	10	6	11	733 239 159	9.800	733 239 179	9.800
50	90	10	6	11	733 239 160	11.800	733 239 180	11.800
63	110	10	6	11	733 239 161	13.200	733 239 181	13.200

d (mm)	D1 (mm)	ZA 1 (mm)	ZA 2 (mm)	Zi 1 (mm)	Zi 2 (mm)	H (mm)	H1 (mm)	H2 (mm)
20	66	255	330	287.0	329	222	182	85
25	66	255	330	289.0	327	222	182	85
32	81	275	355	311.0	350	234	194	105
40	97	325	410	364.0	403	244	210	123
50	118	340	425	382.5	415	244	210	123
63	139	350	480	398.0	466	244	210	123

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>