



PROGEF Standard installation fitting type 311 PN10

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512

Attention:

- sensor length depends on installation fitting

Model:

- Material: PP-H
- Threaded outlet 1 1/4" NPSM
- Suitable for backing flanges metric and inch
- Suitable for SDR 11 - SDR 17.6
- Delivered with profile O-ring

d (inch)	d (mm)	DN (mm)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
2 1/2	75	65	727 311 012	0.430	727 311 042	0.460
3	90	80	727 311 013	0.528	727 311 043	0.542
4	110	100	727 311 014	0.652	727 311 044	0.668
	125	100	727 311 015	0.565	727 311 045	0.595
5	140	125	727 311 016	0.816	727 311 046	0.842
6	160	150	727 311 017	0.983	727 311 047	0.984
	180	150	727 311 018	0.828	727 311 048	0.868
8	200	200	727 311 019	1.524	727 311 049	1.578
8	225	200	727 311 020	1.278	727 311 050	1.332
10	250	250	727 311 021	2.133	727 311 051	2.209
10	280	250	727 311 022	1.760	727 311 052	1.836
12	315	300	727 311 023	2.409	727 311 053	2.495

d (inch)	d (mm)	D (mm)	L (mm)	L1 (mm)	H (mm)	Sensor Type
2 1/2	75	88	48	61	133	flow X1
3	90	102	48	69	140	flow X1
4	110	132	48	79	149	flow X1
	125	132	48	79	144	flow X1
5	140	157	48	94	149	flow X1
6	160	182	48	106	156	flow X1
	180	182	48	106	163	flow X1
8	200	236	48	134	170	flow X1
8	225	236	48	134	178	flow X1
10	250	289	48	160	263	flow X2
10	280	289	48	160	273	flow X2
12	315	329	48	185	285	flow X2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>