



3-Way ball valve type 543 Pro P PVC-U

Horizontal/T-port

DA (Double acting)

Without manual override

With solvent cement spigots metric

Model:

- Control pressure supply through integrated NAMUR interface according VDI/VDE 3845 with 5.6 bar (81.2 psi)
- Basic position A-B-C opened, activated position B-C opened, see flow scheme
- Control time 90° <) 1-2s
- For easy installation and removal
- Integrated stainless steel mounting inserts
- Full plastic solution (actuator housing made of PP-GF)
- Visual position indicator
- Z-dimension, valve end and union nut are compatible with types 285 – 288 and 543 (1st Generation)

Option:

- Position feedback sensor, incl. LED feedback (DN10-50) - PNP, NPN and NAMUR
- Positioner RPC, RPC D, RPC PID
- Individual configuration of the valve

d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	(Δp=1 bar)	Code		(kg)	Code		(kg)
16	10	3/8	10	140	199 295 222	1	0.930	199 295 232	1	0.930
20	15	1/2	10	200	199 295 223	1	0.939	199 295 233	1	0.939
25	20	3/4	10	470	199 295 224	1	1.072	199 295 234	1	1.072
32	25	1	10	793	199 295 225	1	1.266	199 295 235	1	1.266
40	32	1 1/4	10	1290	199 295 226	1	2.125	199 295 236	1	2.125
50	40	1 1/2	10	1910	199 295 227	1	2.609	199 295 237	1	2.609
63	50	2	10	3100	199 295 228	1	4.009	199 295 238	1	4.009

d	Actuator	D	H	H1	H2	H3	H4	H5	H6	L	L1	L2	L3	L4	L6
(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	PPA08	50	157	28	62	95	41	75	8	131	128	73	36	25	74
20	PPA08	50	157	28	62	95	41	75	8	141	128	73	36	25	74
25	PPA08	58	166	32	71	95	41	75	8	165	128	86	43	25	74
32	PPA08	68	166	36	71	95	41	75	8	182	128	99	50	25	74
40	PPA15	84	192	45	84	108	45	88	9	209	165	120	60	45	94
50	PPA15	97	192	51	84	108	45	88	9	242	165	137	69	45	94
63	PPA40	124	237	65	106	131	56	111	9	302	184	179	89	45	120

d	L7	M	closest
(mm)	(mm)		inch
16	32	6	3/8
20	32	6	1/2
25	32	6	3/4
32	32	6	1
40	38	8	1 1/4
50	38	8	1 1/2
63	47	8	2

Data sheet

valid from: 4/3/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>