



JRG Dämmschalen für Ventile EPP

- Passend zu Gewinde Ventilen (1610, 1812, 5200, 5221, 5266), Ventile mit Flansch (1614, 1814, 5204, 5220, 5264) und Ventilen mit Pressübergang (5207, 5208, 5227, 5228, 5229)
- Werkstoff: Expandiertes Polypropylen (EPP)
- Temperatur: max. 110°C
- Wärmeleitfähigkeit: 0.035 W/mK (nach EN 12667)
- Baustoffklasse: B2 (nach DIN 4102) bzw. E (nach EN 13501-1)

DN (mm)	JRG NPK Code	GF Code	PF NPK	SP	Gewicht (kg)	d1 (mm)	l (mm)	l1 (mm)
15	5289.240	351 615 674	2 J1 J75 001	0	0.0110	62	99	95
20	5289.320	351 620 674	2 J1 J75 001	0	0.0140	68	112	105
25	5289.400	351 625 674	2 J1 J75 001	0	0.0334	95	132	137
32	5289.480	351 632 674	2 J1 J75 001	0	0.0704	122	162	172
40	5289.560	351 640 674	2 J1 J75 001	0	0.0915	134	174	190
50	5289.640	351 650 674	2 J1 J75 001	0	0.1551	164	194	233
65	5289.720	351 665 674	2 J3 J77 110	0	0.2116	180	238	253
80	5289.800	351 680 674	2 J3 J77 110	0	0.3282	210	276	290

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>