



ecoFIT pipe PE100 SDR9 / PN20 / S4

Model:

- Material: PE100
- Colour: black
- Dimensions: according to EN 12201-2
- Pipe length: 6m or 12.5m
- Application: for industrial application
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above EN and our technical documentation). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.

Option:

- Other diameter, length, SDR rate, colour stripe, and special marking are available upon request.

d	SDR	PN	Code	Weight	e	Length
(mm)		(bar)		(kg/m)	(mm)	(m)
355	9	20	193 217 118	39.500	39.7	6.0
400	9	20	193 217 119	50.100	44.7	6.0
450	9	20	193 217 120	63.400	50.3	6.0
500	9	20	193 217 121	78.100	55.8	6.0
560	9	20	193 217 122	98.000	62.5	6.0
630	9	20	193 217 123	118.700	70.3	6.0
710	9	20	193 217 124	150.800	79.3	6.0
800	9	20	193 217 125	191.400	89.3	6.0
900	9	20	193 217 126	242.300	101.0	6.0
355	9	20	193 218 118	39.500	39.7	12.5
400	9	20	193 218 119	50.100	44.7	12.5
450	9	20	193 218 120	63.400	50.3	12.5
500	9	20	193 218 121	78.100	55.8	12.5
560	9	20	193 218 122	98.000	62.5	12.5
630	9	20	193 218 123	118.700	70.3	12.5
710	9	20	193 218 124	150.800	79.3	12.5
800	9	20	193 218 125	191.400	89.3	12.5
900	9	20	193 218 126	242.300	101.0	12.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>