





ELGEF Plus Y-Tapping Saddle PE100 d180-315mm / SDR11

- 10 bar Gas / 16 bar Water
- Quick & easy assembly with lever system
- Leakage free hot-tapping with integrated cutter and fix end stops
- Low installation height
- Excellent flow characteristics
- Tapping dome compatible to weld with ELGEF Plus cap for additional access safety: Cap 753961610 (for Do3=32mm) / Cap 753961611 (for Do3=63mm)
- Pressure test cap as accessory: 799199290
- 4 mm pin connectors, limited path fusion indicators
- O-ring-sealed screw plug
- Tapping with key SW17



d (mm)	d1 (mm)	SDR	PN (bar)	DN (mm)	Code	Weight (kg)
180	32	11	16	150	193 136 104	0.605
180	63	11	16	150	193 136 107	1.014
200	32	11	16	200	193 136 114	0.608
200	63	11	16	200	193 136 117	1.022
225	32	11	16	200	193 136 124	0.628
225	63	11	16	200	193 136 127	1.046
250	32	11	16	250	193 136 134	0.661
250	63	11	16	250	193 136 137	1.079
280	63	11	16	250	193 136 147	1.093
315	63	11	16	300	193 136 157	1.094



d (mm)	d1 (mm)	Db (mm)	H (mm)	H4 (mm)	H3 (mm)	L4 (mm)	L (mm)	W (mm)	SDR pipe
180	32	25	175	50	40	76	254	132	11 - 17.6
180	63	31	200	42	48	96	320	132	11 - 17.6
200	32	25	180	55	45	76	263	132	11 - 26
200	63	31	205	53	47	96	328	132	11 - 26
225	32	25	187	62	51	76	274	132	11 - 26
225	63	31	211	54	59	96	339	132	11 - 26
250	32	25	192	68	57	76	285	132	11 - 26
250	63	31	217	60	65	96	350	132	11 - 26
280	63	31	224	67	73	96	362	132	11 - 26
315	63	31	234	76	82	96	418	132	11 - 26

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>