




COOL-FIT 4.0 T90° reduced d75 – d225

Model:

- Pre-insulated PE100 **SDR11**, metric
- Insulation made from PUR foam
- Outer jacket impact and UV resistant. Color: Black
- # as long as stocks last



d/D (mm)	d1/D1 (mm)	SDR	PN (bar)	Code	weight (lb)
75/140	63/125	11	16	738 203 218	1.903
90/160	63/125	11	16	738 203 222	2.716
90/160	75/140	11	16	738 203 223	2.851
110/180	63/125	11	16	738 203 227	4.348
110/180	75/140	11	16	738 203 228	4.297
110/180	90/160	11	16	738 203 229	4.491
160/250	63/125	11	16	738 203 247	11.354
160/250	90/160	11	16	738 203 249	11.347
160/250	110/180	11	16	738 203 250	11.508
160/250	140/200	11	16	738 204 251	12.214
225/315	63/125	11	16	738 203 264	37.108
225/315	90/160	11	16	738 203 266	37.234
225/315	110/180	11	16	738 203 267	37.049
225/315	140/200	11	16	738 204 268	37.699
225/315	160/250	11	16	738 203 269	40.786
160/250	63/125	11	16	738 203 447	9.370
160/250	90/160	11	16	738 203 449	9.744
160/250	110/180	11	16	738 203 450	10.119

d/D (mm)	d1/D1 (mm)	D2 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)	z1 (mm)	closest inch (inch)	Type
75/140	63/125	147	116	55	48	36	228	2 ½	A
90/160	63/125	168	130	62	48	43	253	3 - 2	A
90/160	75/140	168	130	62	55	43	252	3 - 2 ½	A
110/180	63/125	188	154	72	48	57	267	4 - 2	A
110/180	75/140	188	154	72	55	57	268	4 - 2 ½	A
110/180	90/160	188	154	72	62	57	268	4 - 3	A
160/250	63/125	258	192	90	48	77	327	6 - 2	A
160/250	90/160	258	192	90	62	77	327	6 - 3	A
160/250	110/180	258	192	90	72	77	325	6 - 5	A
160/250	140/200	258	192	90	84	77	340	6 - 5	A
225/315	63/125	324	355	110	48	220	412	8 - 2	A
225/315	90/160	324	355	110	62	220	412	8 - 3	A
225/315	110/180	324	355	110	72	220	412	8 - 4	A
225/315	140/200	324	335	110	84	220	412	8 - 5	A
225/315	160/250	324	355	110	90	220	396	8 - 6	A
160/250	63/125	258	192	90	48	77	221	6 - 1	
160/250	90/160	258	192	90	62	77	235	6 - 3	
160/250	110/180	258	192	90	72	77	245	6 - 5	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>