




Line strainer type 305 PVC-U With solvent cement spigots metric

Model:

- Protects valves, pumps, etc. from becoming soiled
- Easy dismantling for cleaning the screens
- **Screen perforation need be ordered separately**
- Overall length according to EN 558

d (mm)	DN (mm)	Size (inch)	PN (bar)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
20	15	½	10	161 305 300	1	0.101	161 305 349	1	0.134
25	20	¾	10	161 305 350	1	0.141	161 305 399	1	0.215
32	25	1	10	161 305 400	1	0.226	161 305 449	1	0.257
40	32	1 ¼	10	161 305 450	1	0.348	161 305 499	1	0.386
50	40	1 ½	10	161 305 500	1	0.600	161 305 549	1	0.632
63	50	2	10	161 305 550	1	0.985	161 305 599	1	1.045
75	65	2 ½	10	161 305 600	1	1.868	161 305 649	1	1.871
90	80	3	10	161 305 650	1	2.590	161 305 699	1	2.585

d (mm)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	closest inch (inch)
20	43	65	124	130	28	½
25	47	76	144	150	37	¾
32	56	90	154	160	37	1
40	64	104	174	180	44	1 ¼
50	82	124	194	200	48	1 ½
63	95	148	224	230	60	2
75	106	188	284	290	74	2 ½
90	120	205	300	310	85	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>