


overgangsknie 90° PE/staal (RVS 1.4305), buitendraad met geïntegreerde kleminrichting



- 10 bar gas / 16 bar water
- met geïntegreerde kleminrichting
- 4 mm stekkeraansluiting
- begrensd lasindicator
- wordt geleverd als kit



d	Thread Type	Inch	DN	PN	code	gewicht	Do	L1	P1	SLW	SDR pipe
(mm)		(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	
20	R	½	15	16	724 100 756	0,211	31	96	32	30	9-11
25	R	¾	20	16	724 100 757	0,230	36	97	32	35	9-11
32	R	1	25	16	724 100 758	0,324	44	98	34	40	9-11
40	R	1 ¼	32	16	724 100 759	0,560	54	109	38	50	9-11
50	R	1 ½	40	16	724 100 760	0,701	66	118	42	60	9-11
63	R	2	50	16	724 100 761	1,105	81	132	46	70	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>