


Transition coupler PE/brass (Ms 58) Male thread



- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4mm pin connectors
- Limited path fusion indicators
- Supplied as a kit with ELGEF Plus coupler or *ELGEF Plus reducer



d	Thread Type	Size	DN	PN	Code	Weight	Do	Lmax	P1	SLW	SDR pipe
(mm)		(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	
20	R	½	15	16	720 920 756	0.187	31	110	34	30	9-11
20	R	1	15	16	720 920 754	0.344	44	124	34	40	9-11
25	R	¾	20	16	720 920 757	0.254	36	111	34	35	9-11
25	R	1	20	16	720 920 763	0.340	44	124	34	40	9-11
32	R	½	25	16	720 920 764	0.213	44	121	34	30	9-11
32	R	¾	25	16	720 920 765	0.268	44	122	34	35	9-11
32	R	1	25	16	720 920 758	0.340	44	117	34	40	9-11
32	R	1 ¼	25	16	720 920 766	0.489	54	135	34	50	9-11
32	R	1 ½	25	16	720 920 767	0.635	60	143	34	60	9-11
32	R	2	25	16	720 920 768	1.000	81	157	34	70	9-11
40	R	1	32	16	720 920 771	0.364	54	133	39	40	9-11
40	R	1 ¼	32	16	720 920 759	0.514	54	127	39	50	9-11
40	R	1 ½	32	16	720 920 772	0.645	66	143	39	60	9-11
40	R	2	32	16	720 920 773	0.961	81	157	39	70	9-11
50	R	1	40	16	720 920 776	0.367	66	141	43	40	9-11
50	R	1 ¼	40	16	720 920 777	0.554	66	143	43	50	9-11
50	R	1 ½	40	16	720 920 760	0.652	66	135	43	60	9-11
50	R	2	40	16	720 920 778	0.971	81	157	43	70	9-11
63	R	1	50	16	720 920 781	0.441	81	151	46	40	9-11
63	R	1 ¼	50	16	720 920 782	0.600	81	153	46	40	9-11
63	R	1 ½	50	16	720 920 783	0.712	81	153	46	60	9-17.6
63	R	2	50	16	720 920 761	0.943	81	147	46	70	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>