


aansluitzadel met versterkingsring en RVS-bouten

- water PN16-10
- geschikt voor PE en PVC buis
- materiaal: PP
- female thread: ISO 7 (parallel)
- afdichting: O-ring NBR
- versterkingsring: RVS AISI430
- bouten en moeren: RVS (bouten: A2-AISI304; moeren: A4-AISI316)
- kleur: blauw
- B= aantal bouten
- M= bouttype
- met O-ring (*)

	d	Rp	PN	B	M	code	SP	GP	gewicht
	(mm)	(inch)	(bar)						(kg)
*	20	½	16	2	M8X40	727 627 001	1		0,119
*	25	½	16	2	M8X30	727 627 011	1		0,110
*	25	¾	16	2	M8X30	727 627 012	1		0,123
*	32	½	16	2	M8X30	727 627 021	1		0,099
*	32	¾	16	2	M8X30	727 627 022	1		0,115
*	32	1	16	2	M8X40	727 627 023	1		0,151
	40	½	16	2	M8X40	727 627 031	1		0,135
	40	¾	16	2	M8X40	727 627 032	1		0,148
	40	1	16	2	M8X40	727 627 033	1		0,155
	50	½	16	4	M8X40	727 627 041	1		0,200
	50	¾	16	4	M8X40	727 627 042	1		0,213
	50	1	16	4	M8X40	727 627 043	1		0,207
	50	1 ¼	16	4	M8X40	727 627 044	1		0,225
	63	½	16	4	M8X40	727 627 051	1		0,216
	63	¾	16	4	M8X40	727 627 052	1		0,215
	63	1	16	4	M8X40	727 627 053	1		0,226
	63	1 ¼	16	4	M8X40	727 627 054	1		0,265
	63	1 ½	16	4	M8X40	727 627 055	1		0,279
	75	½	16	4	M8X60	727 627 061	1		0,367
	75	¾	16	4	M8X60	727 627 062	1		0,370
	75	1	16	4	M8X60	727 627 063	1		0,384
	75	1 ¼	16	4	M8X60	727 627 064	1		0,407
	75	1 ½	16	4	M8X60	727 627 065	1		0,428
	75	2	16	4	M8X60	727 627 066	1		0,437
	90	½	16	4	M8X60	727 627 071	1		0,412
	90	¾	16	4	M8X60	727 627 072	1		0,414
	90	1	16	4	M8X60	727 627 073	1		0,422
	90	1 ¼	16	4	M8X60	727 627 074	1		0,455
	90	1 ½	16	4	M8X60	727 627 075	1		0,467
	90	2	16	4	M8X60	727 627 076	1		0,480
	110	½	16	6	M8X50	158 050 498	1		0,509
	110	¾	16	6	M8X50	727 627 082	1		0,515
	110	1	16	6	M8X50	727 627 083	1		0,505
	110	1 ¼	16	6	M8X50	727 627 084	1		0,543
	110	1 ½	16	6	M8X50	727 627 085	1		0,545
	110	2	16	6	M8X50	727 627 086	1		0,570
	110	3	6	6	M8X70	727 627 087	1		1,094
	125	½	16	6	M8X50	727 627 091	1		0,578
	125	¾	16	6	M8X50	727 627 092	1		0,590
	125	1	16	6	M8X50	727 627 093	1		0,592
	125	1 ¼	16	6	M8X50	727 627 094	1		0,612
	125	1 ½	16	6	M8X50	727 627 095	1		0,620
	125	2	16	6	M8X50	727 627 096	1		0,641
	125	3	6	6	M8X70	727 627 097	1		1,001
	125	4	6	6	M8X70	727 627 098	1		1,037
	140	½	16	6	M8X70	727 627 101	1		0,838

Data sheet

valid from: 01-08-2024




d	Rp	PN	B	M	code	SP	GP	gewicht
(mm)	(inch)	(bar)						(kg)
140	¾	16	6	M8X70	727 627 102	1		0,836
140	1	16	6	M8X70	727 627 103	1		0,838
140	1 ¼	16	6	M8X70	727 627 104	1		0,880
140	1 ½	16	6	M8X70	727 627 105	1		0,807
140	2	16	6	M8X70	727 627 106	1		0,898
140	3	10	6	M8X70	727 627 107	1		1,132
140	4	10	6	M8X70	727 627 108	1		1,196
160	½	16	6	M8X70	727 627 111	1		0,885
160	¾	16	6	M8X70	727 627 112	1		0,908
160	1	16	6	M8X70	727 627 113	1		0,917
160	1 ¼	16	6	M8X70	727 627 114	1		0,920
160	1 ½	16	6	M8X70	727 627 115	1		0,931
160	2	16	6	M8X70	727 627 116	1		0,956
160	3	10	6	M8X70	727 627 117	1		1,185
160	4	10	6	M8X70	727 627 118	1		1,238
*	180	1	10	M10x80	727 627 123	1		1,941
*	180	1 ¼	10	M10x80	727 627 124	1		1,978
*	180	1 ½	10	M10x80	727 627 125	1		1,980
*	180	2	10	M10x80	727 627 126	1		2,002
*	180	3	10	M10x80	727 627 127	1		2,001
*	180	4	10	M10x80	727 627 128	1		2,055
*	200	1 ½	10	M10x80	727 627 135	1		1,935
*	200	2	10	M10x80	727 627 136	1		1,933
*	200	3	10	M10x80	727 627 137	1		1,980
*	200	4	10	M10x80	727 627 138	1		1,975
*	225	1 ½	10	M10x80	727 627 145	1		2,045
*	225	2	10	M10x80	727 627 146	1		2,070
*	225	3	10	M10x80	727 627 147	1		2,150
*	225	4	10	M10x80	727 627 148	1		2,184
*	250	2	10	M10x80	727 627 156	1		2,431
*	250	3	10	M10x80	727 627 157	1		2,466
*	250	4	10	M10x80	727 627 158	1		2,462
	280	2	10	M10x160	727 627 166	1		3,440
*	280	3	10	M10x160	727 627 167	1		3,505
*	280	4	10	M10x160	727 627 168	1		3,585
	315	2	10	M10x110	727 627 176	1		4,156
*	315	3	10	M10x110	727 627 177	1		4,230
*	315	4	10	M10x110	727 627 178	1		4,263


d	Rp	d1	L	L1	H	H1
(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)
*	20	½	12	46	77	26
*	25	½	13	49	79	15
*	25	¾	13	49	79	15
*	32	½	14	49	79	20
*	32	¾	14	49	79	20
*	32	1	14	62	87	20
	40	½	21	62	86	20
	40	¾	21	62	86	20
	40	1	21	62	86	20
	50	½	21	62	86	20
	50	¾	21	62	86	20
	50	1	21	62	86	20
	50	1 ¼	21	62	86	20
	63	½	18	62	101	21
	63	¾	24	62	101	21
	63	1	31	62	101	21
	63	1 ¼	31	62	101	21
	63	1 ½	31	62	101	21

Data sheet

valid from: 01-08-2024



d	Rp	d1	L	L1	H	H1
(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)
75	½	16	79	123	102	14
75	¾	21	79	123	104	16
75	1	27	79	123	107	19
75	1 ¼	35	79	123	109	21
75	1 ½	42	79	123	109	21
75	2	53	79	123	112	24
90	½	16	87	138	116	14
90	¾	21	87	138	118	16
90	1	27	87	138	121	19
90	1 ¼	35	87	138	123	21
90	1 ½	42	87	138	123	21
90	2	53	87	138	126	24
110	½	15	99	152	150	23
110	¾	20	99	152	150	23
110	1	26	99	152	150	23
110	1 ¼	35	99	152	150	23
110	1 ½	41	99	152	150	23
110	2	51	99	152	150	23
110	3	85	99	152	150	23
125	½	15	101	166	169	24
125	¾	20	101	166	169	24
125	1	26	101	166	169	24
125	1 ¼	35	101	166	168	23
125	1 ½	41	101	166	168	23
125	2	50	101	166	168	23
125	3	85	139	178	180	37
125	4	90	139	178	181	38
140	½	18	114	207	191	25
140	¾	24	114	207	191	25
140	1	30	114	207	191	25
140	1 ¼	38	114	207	191	25
140	1 ½	45	114	207	191	24
140	2	50	114	207	191	24
140	3	85	142	208	201	38
140	4	90	142	208	201	38
160	½	18	114	226	215	24
160	¾	24	114	226	215	24
160	1	30	114	226	215	24
160	1 ¼	37	114	226	215	24
160	1 ½	45	114	226	215	24
160	2	51	114	226	215	24
160	3	84	142	228	222	24
160	4	90	142	228	222	24
* 180	1	30	169	262	265	38
* 180	1 ¼	36	169	262	265	38
* 180	1 ½	42	169	262	265	38
* 180	2	54	169	262	265	38
* 180	3	84	169	262	265	38
* 180	4	108	169	262	265	38
* 200	1 ½	45	169	262	265	38
* 200	2	54	169	262	265	38
* 200	3	85	169	262	265	38
* 200	4	103	169	262	267	40
* 225	1 ½	45	174	287	287	26
* 225	2	51	174	287	287	26
* 225	3	85	174	287	295	37
* 225	4	103	174	287	295	38
* 250	2	55	178	310	314	38
* 250	3	85	178	310	314	38



	d	Rp	d1	L	L1	H	H1
	(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)
*	250	4	103	178	310	314	38
	280	2	51	179	335	326	31
*	280	3	78	179	335	338	41
*	280	4	98	179	335	338	46
	315	2	51	246	390	350	31
*	315	3	78	246	390	363	41
*	315	4	98	246	390	363	46

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>