




PROGEF Standard Lug-style end installation butterfly valve type 244
FC (Fail safe to close)
Flange standard ANSI/ASME

Model:




- Overall length according to EN 558, ISO 5752
- Connecting dimension: ANSI/ASME B 16.5 Class 150
- Control pressure supply through integrated NAMUR interface according VDI/VDE 3845 with 4.2 bar (60.9 psi)
- Control time 90° < 1-2s
- For easy installation and removal
- Full plastic solution (actuator housing made of PP-GF)
- Visual position indicator

Option:

- Optional accessory: Valve-Integrated position feedback with limit switches (limit switches have to be ordered separately)
- Positioner RPC, RPC D, RPC PID
- Individual configuration of the valve

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d	Size	DN	PN	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(inch)	(mm)	(bar)	Code		(kg)	Code		(kg)
63	2	50	10	199 244 802	1	3.499	199 244 822	1	3.499
75	2 ½	65	10	199 244 803	1	3.656	199 244 823	1	3.656
90	3	80	10	199 244 804	1	4.600	199 244 824	1	4.692
110	4	100	10	199 244 805	1	6.406	199 244 825	1	6.406
140	5	125	10	199 244 806	1	9.222	199 244 826	1	9.222

d	Hmax	Lmax	Wmax	U	V	H4	V1	Lg	D2	Q1	Q2	d2	k
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)
63	338.1	245.5	165	90	133.3	23	78.8	44.7	160	40		UNC 5/8	120.7
75	351.0	245.5	182	90	139.9	23	85.1	45.7	180	54	35	UNC 5/8	139.7
90	367.8	343.0	210	90	145.6	23	91.2	48.7	195	67	50	UNC 5/8	152.4
110	404.5	343.0	240	90	166.0	23	107.5	55.6	226	88	74	UNC 5/8	190.5
140	433.7	343.0	272	90	180.0	23	122.7	63.5	258	113	97	UNC 3/4	215.9

d	Y	E	Y1	M2
(mm)	(mm)	(mm)	(mm)	(mm)
63	111	119.5	15	122.75
75	111	119.5	15	122.75
90	131	141.5	15	171.50
110	131	141.5		171.50
140	131	141.5		171.50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 2/8/25



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>