




PROGEF Standard Ball valve type 180
100-230V
With manual emergency override
With butt fusion spigots PP-H SDR11 ISO

Model:

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close/ Middle)
- Integrated stainless steel mounting inserts

Option:


- Other valve and actuator configurations available
- Optional accessories: Monitoring board, Positioner, Profibus DP board, Modbus TCP EA 25-250 Ethernet Interface Card




DN65-100

Data sheet


valid from: 2/8/25



d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	SDR	EPDM Code	Weight (kg)
20	15	10	185	11	199 180 323	2.100
25	20	10	350	11	199 180 324	2.200
32	25	10	700	11	199 180 325	2.300
40	32	10	1000	11	199 180 326	2.600
50	40	10	1600	11	199 180 327	2.952
63	50	10	3100	11	199 180 328	3.800
75	65	10	5000	11	199 180 329	6.200
90	80	10	7000	11	199 180 330	7.200
110	100	10	11000	11	199 180 331	11.200



d (mm)	Actuator	B3 (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	L (mm)	L1 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	s1 (mm)
20	EA25	25	50	122	M6	227	27	12	130	33	28	180	97	83	1.9
25	EA25	25	58	122	M6	231	30	12	143	33	33	180	97	83	2.3
32	EA25	25	68	122	M6	237	36	12	150	33	36	180	97	83	3.0
40	EA25	45	84	122	M8	243	44	15	171	33	43	180	97	83	3.7
50	EA25	45	97	122	M8	249	51	15	191	33	45	180	97	83	4.6
63	EA25	45	124	122	M8	264	64	15	220	33	51	180	97	83	5.8
75	EA45	70	166	122	M8	313	85	15	266	33	68	180	98	82	8.2
90	EA45	70	200	122	M8	325	105	15	264	33	71	180	98	82	10.0
110	EA120	120	238	122	M12	363	123	22	301	33	82	180	98	82	12.0



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>