



ecoFIT Segmented Bend 1.5D 90° PE100 SDR17

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 8 bar water

Note:

* Please call us for availability

	d	Code	Weight	Z	L	R	e
	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)
	90	P2314607090	0.90	348	150	198.0	5.4
	110	P2314607110	1.65	420	200	220.0	6.6
	125	P2314607125	2.10	425	200	225.0	7.4
	140	P2314607140	2.64	424	200	224.0	8.3
	160	P2314607160	3.58	448	200	240.0	9.5
	180	P2314607180	4.82	473	200	270.0	10.7
	200	P2314607200	6.31	502	200	300.0	11.9
	225	P2314607225	8.45	537	200	337.5	13.4
	250	P2314607250	12.25	622	250	375.0	14.8
	280	P2314607280	16.24	663	250	420.0	16.6
	315	P2314607315	25.69	821	350	472.5	18.7
	355	P2314607355	34.73	883	350	532.5	21.1
	400	P2314607400	47.03	950	350	600.0	23.7
	450	P2314607450	63.93	1025	350	675.0	26.7
	500	P2314607500	88.98	1150	400	750.0	29.7
	560	P2314607560	119.07	1240	400	840.0	33.2
	630	P2314607630	169.51	1395	450	945.0	37.4
	710	P2314607710	242.54	1565	500	1065.0	42.1
	800	P2314607800	364.51	1850	650	1200.0	47.4
	900	P2314607900	511.81	2050	700	1350.0	53.3
	1000	P2314607001	676.74	2200	700	1500.0	59.3
*	1200	P2314607002	1184.61	2500	700	1800.0	71.1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>