





**kogelkraan type 375, PVC-U
met draadmof, Rp**

Uitvoering:

- True double union safe block ball valve
- kogelafdichting uit PTFE
- Handle includes integrated tool for ball seat adjustment
- Very compact dimensions
- z-maat, inlegdelen en wartelmoeren zijn niet compatibel met type 546

toepassing:

- Basic industrial applications without automation



d (mm)	DN (mm)	Thread Type	Inch (inch)	PN (bar)	kv-waarde ($\Delta p=1$ bar) (l/min)	EPDM code	SP	gewicht (kg)
75	65	Rp	2 1/2	10	5000	161 375 528	1	2,132
90	80	Rp	3	10	7000	161 375 529	1	2,132
110	100	Rp	4	10	11000	161 375 530	1	5,793

FKM code	SP	gewicht (kg)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	z (mm)
161 375 538	1	2,132	145	129	184	179	110	103	118
161 375 539	1	3,213	168	143	212	209	128	120	140
161 375 540	1	5,793	210	169	244	250	150	141	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>