

Installation fitting type 310 PVC-U For socket systems metric



Range of use:


- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735

Attention:

- sensor length depends on installation fitting

Model:

- Threaded outlet 1 1/4" NPSM
- Union end with solvent cement socket PVC-U



d (mm)	DN (mm)	PN (bar)	Type	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
20	15	16	PVMT005	721 310 006	1	0.181	721 310 036	1	0.181
25	20	16	PVMT007	721 310 007	1	0.226	721 310 037	1	0.226
32	25	16	PVMT010	721 310 008	1	0.303	721 310 038	1	0.304
40	32	16	PVMT012	721 310 009	1	0.419	721 310 039	1	0.479
50	40	16	PVMT015	721 310 010	1	0.568	721 310 040	1	0.571
63	50	16	PVMT020	721 310 011	1	0.879	721 310 041	1	0.881

d (mm)	DN (mm)	L (mm)	L1 (mm)	D (mm)	H (mm)	z (mm)	Sensor Type
20	15	128	90	43	76	48	flow X0, pH XX
25	20	144	100	51	78	53	flow X0, pH XX
32	25	160	110	58	81	58	flow X0, pH XX
40	32	168	110	72	85	58	flow X0, pH XX
50	40	188	120	83	89	63	flow X0, pH XX
63	50	212	130	100	95	68	flow X0, pH XX

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>