



ecoFIT Ball Valve type 546 Pro PP-H
With butt fusion spigots PE100 SDR17.6 ISO

Model:

- Lockable lever as standard
- Ball seat PTFE
- Integrated stainless steel mounting inserts
- Z-dimension, valve end and union nut **are compatible** with type 546 (1st Generation)


Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of valves possible



d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
50	40	1 1/2	10	1600	167 546 126	1	0.620	167 546 136	1	0.620
63	50	2	10	3100	167 546 127	1	1.200	167 546 137	1	1.200

d	B3	DE1	G	H	H1	H4	L	Lz	M	M1	M2	s1
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
50	45	97	M8	101.5	51	15	191	45	131	57	74	2.9
63	45	124	M8	116.5	64	15	220	51	152	66	86	3.6



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>