



Branch saddles topload Outlet 315 mm

- 10 bar Gas / 16 bar Water
- Branch Saddle installation only with installation set Topload TL500 (799.300.809)
- Angle adaptors (799 350 340) for fusion cable required
- 4mm pin connectors
- Spigot outlet for butt- and electrofusion
- Full pressure applicable - no derating factor
- With integrated thread for pressure test with separate pressure test cap 799.199.288 (outlet d315) / 799.199.289 (outlet d500)



d	d2	Do1	DN	PN	Code	Weight	Lmax	Q1	W	H	Hmax	SDR pipe
(mm)	(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	
450	232	315	450	16	193 135 436	18.500	500	174	500	216	346	11 - 26
500	232	315	500	16	193 135 446	17.000	500	174	500	216	337	11 - 26
560	232	315	600	16	193 135 456	16.100	500	174	500	216	327	11 - 26
630	232	315	600	16	193 135 466	15.950	500	174	500	216	312	11 - 33
710	232	315	700	16	193 135 476	14.800	500	174	500	216	297	11 - 33
800	232	315	800	16	193 135 486	14.300	500	174	500	216	287	11 - 33
900	232	315	900	16	193 135 496	13.800	500	174	500	216	281	11 - 33
1000	232	315	1000	16	193 135 506	13.500	500	174	500	216	274	11 - 33

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>