



Type 2260 Level Transmitter, Continuous Measuring, Display Version, 4-20 mA / HART, ATEX approval

- Principle: non-contact ultrasonic transit time
- Measuring range: 0.2...4 m, 0.25...6 m, 0.45...15 m
- Sensor Type: PVDF
- Output: 4-20 mA, 2-wire; HART Protocol
- Integrated display and programming buttons
- Supply power: 12...30 V DC
- ATEX II 1 G EEx ia II B T6

Operating Range	Process Connection	Process Connection Size	Communication Interface	Electrical connection	MFR #
0.2 - 4 m	1 1/2" BSP	NPT 1.5"	4-20 mA, HART / Ex	Terminal	2260-V-1DBX-4
0.25 - 6 m	2" BSP	NPT 2"	4-20 mA, HART / Ex	Terminal	2260-V-1DBX-6
0.45 - 15 m	DN 125 flange	DN125	4-20 mA, HART / Ex	Terminal	2260-V-1DFX-15
0.2 - 4 m	1 1/2" NPT	NPT 1.5"	4-20 mA, HART / Ex	Terminal	2260-V-1DNX-4
0.25 - 6 m	2" NPT	NPT 2"	4-20 mA, HART / Ex	Terminal	2260-V-1DNX-6
0.45 - 15 m	ANSI Flange 5 inch	ANSI 5"	4-20 mA, HART / Ex	Terminal	2260-V-1DAX-15

Measuring range (m)	Sensor Type	Code	Weight (kg)	PF
0.20 - 4.00	PVDF	159 300 112	5.000	3 86 376 005
0.25 - 6.00	PVDF	159 300 113	5.000	3 86 376 005
0.45 - 15.00	PVDF	159 300 114	5.000	3 86 376 005
0.20 - 4.00	PVDF	159 300 142	0.790	3 86 376 005
0.25 - 6.00	PVDF	159 300 143	0.790	3 86 376 005
0.45 - 15.00	PVDF	159 300 144	0.790	3 86 376 005

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>