



PVC-C管道，公制
S6.3, SDR13.6, PN16

型号:

- Material: PVC-C, heat resistant
- Dimension: acc. to DIN 8079/80
- Colour: agate grey RAL 7038
- Pipe length: 5000mm, with plain ends
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentation). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.

d	SDR	PN	code	weight	e
(mm)		(bar)		(kg/m)	(mm)
32	13.6	16	163 017 133	0,379	2,4
40	13.6	16	163 017 134	0,582	3,0
50	13.6	16	163 017 135	0,896	3,7
63	13.6	16	163 017 136	1,430	4,7
75	13.6	16	163 017 137	2,020	5,6
90	13.6	16	163 017 138	2,880	6,7
110	13.6	16	163 017 139	4,270	8,1
160	13.6	16	163 017 142	8,980	11,8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>