

Ultrasonic Flowmeter GF U1000 V2

Ultrasonic clamp-on flowmeter with integral design & digital communication options



- Easy to install, compact, robust and reliable - designed for long-term use in industrial applications
- Accurate flow measurement on virtually any pipe - especially configured for pure water applications
- Ready for Industry 4.0 with various communications options. Including: Modbus, 4-20 mA, pulse & alarm output
- Compact 'clamp-on' design with integral head unit
- Large, easy to read graphic display with backlighting



Pipe Outside d	Accuracy	Communication	Power Supply	Data Storage & Export	Heatmeter
d22 - d115	±3% of m.v. for DN100	4-20 mA & Pulse	24 V	-	-
d125 - d180	±3% of m.v. for DN100	4-20 mA & Pulse	24 V	-	-
d22 - d115	±3% of m.v. for DN150	Modbus & Pulse	24 V	-	-
d125 - d180	±3% of m.v. for DN150	Modbus & Pulse	24 V	-	-



Cable length (m)	Code
5	159 300 300
5	159 300 301
5	159 300 302
5	159 300 303



Data sheet

valid from: 4/16/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>