



ecoFIT Segmented Bend 1.5D 45° PE100 SDR9

Model:

- Long spigot for butt- and electrofusion welding
- Production process: segment welded
- Application: Water distribution
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 16 bar water

Note:

* Please call us for availability

d	Code	Weight	Z	L	R	e	
(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	
90	P2317605090	1.17	232	150	198.0	10.1	
110	P2317605110	2.19	291	200	220.0	12.3	
125	P2317605125	2.88	293	200	225.0	14.0	
140	P2317605140	3.61	293	200	224.0	15.7	
160	P2317605160	4.78	299	200	240.0	17.9	
180	P2317605180	6.26	312	200	270.0	20.1	
200	P2317605200	8.12	324	200	300.0	22.4	
225	P2317605225	10.73	340	200	337.5	25.2	
250	P2317605250	15.79	405	250	375.0	27.9	
280	P2317605280	20.59	424	250	420.0	31.3	
315	P2317605315	33.58	546	350	472.5	35.2	
355	P2317605355	44.54	571	350	532.5	39.7	
400	P2317605400	59.65	599	350	600.0	44.7	
450	P2317605450	79.25	630	350	675.0	50.3	
*	500	P2317605500	110.42	711	400	750.0	55.8
*	560	P2317605560	145.34	748	400	840.0	62.5
*	630	P2317605630	206.45	841	450	945.0	70.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>