






DN10/15 - 50



Robinets à bille type 546 PP-H
Avec inserts de fixation
Avec bout à souder pour soudage bout à bout S8/SDR17.6 métrique

Exécution:

- Matériau: PP-H
- Conçu pour un montage et démontage facile
- Joint de la bille en PTFE
- Inserts de fixation en acier inoxydable intégrés
- Cote z, extrémités de la vanne et écrous ne sont **pas compatibles** avec le type 346 (DN10/15-50) et le type 370 (DN65-100)

Option:

- Possibilité de configuration individuelle de la vanne
- Module multifonctions avec contacts fin de course intégrés
- Peut être équipé d'un servomécanisme pneumatique ou électrique de Georg Fischer

d	DN	PN	Valeur-kv	EPDM	CAN	SP	Poids	FKM	CAN	SP	Poids
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code			(kg)	Code			(kg)
			(L/min)								
50	40	6	1600	167 546 066		1	0.635	167 546 076		1	0.635
63	50	6	3100	167 546 067		1	1.159	167 546 077		1	1.200
75	65	6	5000	167 546 068		1	2.575	167 546 078		1	3.387
90	80	6	7000	167 546 069		1	4.731	167 546 079		1	5.500
110	100	6	11000	167 546 070		1	8.600	167 546 080		1	8.600

d	D	H	H1	H2	L	L1	L2	L4	L5	L6	M	e	Pouce
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(inch)
50	97	97	51	15	191	128	89	45	54	74	M8	2.9	1 ½
63	124	116	64	15	220	152	101	45	66	87	M8	3.6	2
75	166	149	85	15	266	270	136	70	64	206	M8	4.7	2 ½
90	200	161	105	15	264	270	141	70	64	206	M8	5.5	3
110	238	178	123	22	301	320	164	120	64	256	M12	6.8	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 25/08/2024



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>