



SYGEF Plus reducer
SDR21/PN16
High Purity clean-room product ISO Class 5 (100)

d - d1 (mm)	FM	Code	weight (lb)	e1 (mm)	e (mm)	L (mm)	L1 (mm)	L2 (mm)
25 - 20	BCF, IR	735 908 600	0.029	1.9	1.9	50	22	22
32 - 20	BCF, IR	735 908 602	0.040	1.9	2.4	50	22	22
32 - 25	BCF, IR	735 908 601	0.042	1.9	2.4	50	22	22
40 - 20	BCF, IR	735 908 605	0.055	1.9	2.4	58	22	24
40 - 25	BCF, IR	735 908 604	0.055	1.9	2.4	55	22	24
40 - 32	BCF, IR	735 908 603	0.064	2.4	2.4	55	22	24
50 - 25	BCF, IR	735 908 608	0.088	1.9	3.0	60	22	25
50 - 32	BCF, IR	735 908 607	0.097	2.4	3.0	60	22	25
50 - 40	BCF, IR	735 908 606	0.101	2.4	3.0	60	22	25
63 - 32	BCF, IR	735 908 611	0.130	2.4	3.0	65	22	25
63 - 40	BCF, IR	735 908 610	0.134	2.4	3.0	65	22	25
63 - 50	BCF, IR	735 908 609	0.154	3.0	3.0	65	22	25
75 - 40	BCF, IR	735 908 614	0.240	2.4	3.6	68	24	25
75 - 50	BCF, IR	735 908 613	0.201	3.0	3.6	65	24	25
75 - 63	BCF, IR	735 908 612	0.209	3.0	3.6	65	24	25
90 - 63	BCF, IR	735 908 616	0.362	3.0	4.3	75	25	30
90 - 75	BCF, IR	735 908 615	0.412	3.6	4.3	75	25	35
110 - 63	BCF, IR	735 908 619	0.527	3.0	5.3	90	30	30
110 - 75	BCF, IR	735 908 618	0.549	3.6	5.3	90	30	35
110 - 90	BCF, IR	735 908 617	0.586	4.3	5.3	90	30	35
140 - 110	IR	735 908 621	1.354	5.3	6.7	110	40	40
160 - 110	IR	735 908 623	1.556	5.3	7.7	120	40	40
160 - 140	IR	735 908 622	1.982	6.7	7.7	120	40	40
200 - 160	IR	735 908 624	3.250	7.7	9.6	145	40	35
225 - 110	IR	735 908 625	3.594	5.3	10.8	160	55	40
225 - 160	IR	735 908 626	3.885	7.7	10.8	160	55	28
225 - 200	IR	735 908 627	4.722	9.6	10.8	160	55	50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>