




Transition coupler PE/brass (Ms 58) Female thread

- PE 100 SDR 11 (ISO S5)
- PE10 SDR16, metric
- With integral pipe fixation
- 4mm pin connectors
- Limited path fusion indicators
- Supplied as a kit



d	Thread Type	Size	DN	PN	Code	weight	Do	Lmax	P1	SLW
(mm)		(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)
32	Rp	1	25	16	720 920 258	0.306	44	108	34	40
40	Rp	1 ¼	32	16	720 920 259	0.496	54	118	39	50
50	Rp	1 ½	40	16	720 920 260	0.725	66	126	43	60
63	Rp	1	50	16	720 920 281	1.300	81	138	46	70
63	Rp	1 ¼	50	16	720 920 282	1.230	81	138	46	70
63	Rp	1 ½	50	16	720 920 283	1.134	81	138	46	70
63	Rp	2	50	16	720 920 261	1.057	81	138	46	70

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>