



installatiefitting type 310, PVC-U voor mofsystemen BS inch

Uitvoering:

- materiaal: PVC-U
- draadaftakking 1 1/4" NPSM
- inlegdeel met lijmmof PVC-U

toepassing:

- compatibel met Signet flowsensoren: type 2551, 2537, 515, 8510, 2536, 8512
- compatibel met Signet pH/ORP sensoren: type 2724, 2725, 2726, 2736, 2735

let op:

- de sensorlengte is afhankelijk van de installatiefitting

DN (mm)	Inch (inch)	PN (bar)	type	EPDM code	SP	gewicht (kg)	FKM code	SP	gewicht (kg)
15	½	15	PVAT005	721 310 306	1	0,181	721 310 336	1	0,181
20	¾	15	PVAT007	721 310 307	1	0,244	721 310 337	1	0,244
25	1	15	PVAT010	721 310 308	1	0,333	721 310 338	1	0,299
32	1 ¼	15	PVAT012	721 310 309	1	0,403	721 310 339	1	0,440
40	1 ½	15	PVAT015	721 310 310	1	0,700	721 310 340	1	0,579
50	2	15	PVAT020	721 310 311	1	1,011	721 310 341	1	1,011

DN (mm)	L (mm)	L1 (mm)	D (mm)	H (mm)	z (mm)	sensor type
15	131	90	43	76	48	flow X0, pH XX
20	147	100	51	78	53	flow X0, pH XX
25	164	110	58	81	58	flow X0, pH XX
32	171	110	72	85	58	flow X0, pH XX
40	188	120	83	89	63	flow X0, pH XX
50	211	130	100	95	68	flow X0, pH XX

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>