



Full face flange ABS Inch BS Drilled to universal standard

Model:

- In accordance with BS 10, DIN EN 1092 and ASME B 16.5
- Jointing face serrated
- It is recommended to use backing flanges in conjunction with all Full Face Flanges
- All Full Face Flanges are manufactured with outside diameter to BS EN 1092
- Solvent cement socket BS inch
- For pressure ratings over 2 bar backing flanges must be used

AL: number of holes

d (inch)	DN (mm)	PN (bar)	Code	SP	Weight (kg)	D3 (mm)	D2 (mm)	D1 (mm)	AL	H1 (mm)	z (mm)	D (mm)	H (mm)
½	15	10	729 733 106	100	0.064	15	27	67	4	21	3	95	10
¾	20	10	729 733 107	20	0.083	15	33	73	4	24	8	105	10
1	25	10	729 733 108	50	0.097	15	41	83	4	27	3	115	10
1 ¼	32	10	729 733 109	30	0.149	15	50	88	4	32	3	140	10
1 ½	40	10	729 733 110	14	0.180	15	61	98	4	33	3	150	10
2	50	10	729 733 111	18	0.230	18	77	115	4	40	3	165	10
3	80	10	729 733 113	8	0.238	18	108	146	4	56	5	200	12
4	100	10	729 733 114	2	0.771	18	136	178	8	69	5	220	17
6	150	10	729 733 117	2	1.486	22	198	235	8	96	5	285	22

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>