






NeoFlow Pressure reducing valve POM-C
Maximum downstream pressure 123 psi(g)

- Available dimensions: 8" – 12"
- Maximum upstream pressure: 232 psi (g)
- Connection type: Wafer Design
- Sealing material: EPDM
- Body material: POM-C
- Components: Stainless Steel
- Thread fittings: NPT
- Medium: Water
- Co-developed with OFUI



Nominal Pipe Diameter	Maximum up-stream pressure (psi(g))	Maximum downstream pressure (psi(g))	Code	weight (lb)
8"	232	123.0	193 174 020	57.3
10"	232	123.0	193 174 022	76.7
12"	232	123.0	193 174 023	156.5

D	Lmax	Lb	Hmax	Wmax
(inch)	(inch)	(inch)	(inch)	(inch)
10.8	11.73	11.73	15.98	19.09
12.9	13.70	13.70	20.08	21.65
14.9	15.67	15.67	23.46	25.20



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>