



Reducing Bushes excentric, PE100 SDR11

Model:

- Conventional butt fusion according to DVS2207
- Machined

d1 (mm)	d2 (mm)	PN (bar)	Code	SP	L (mm)	L1 (mm)	L2 (mm)	e1 (mm)	e2 (mm)
63	50	16	700 647 600	0	120	35	35	5,8	4,6
75	50	16	700 647 601	0	120	40	35	6,8	4,6
75	63	16	700 647 602	0	120	40	35	6,8	5,8
90	63	16	700 647 603	0	140	50	50	8,2	5,8
90	75	16	700 647 604	0	140	50	50	8,2	6,8
110	75	16	700 647 605	0	140	50	50	10	6,8
110	90	16	700 647 606	0	140	50	50	10	8,2
125	90	16	700 647 607	0	140	50	50	11,4	5,1
125	110	16	700 647 608	0	140	50	50	11,4	10
140	90	16	700 647 609	0	140	50	50	12,7	8,2
140	110	16	700 647 610	0	140	50	50	12,7	10
160	90	16	700 647 611	0	140	50	54	14,6	8,2
160	110	16	700 647 612	0	120	40	45	14,6	10
160	125	16	700 647 613	0	110	40	44	14,6	11,4
160	140	16	700 647 614	0	90	40	33	14,6	12,7
180	125	16	700 647 615	0	130	40	52	16,4	11,4
180	140	16	700 647 616	0	110	40	41	16,4	12,7
180	160	16	700 647 617	0	90	40	33	16,4	16,4
200	140	16	700 647 618	0	140	40	50	18,2	12,7
200	160	16	700 647 619	0	120	40	41	18,2	14,6
200	180	16	700 647 620	0	100	40	43	18,2	16,4
225	160	16	700 647 621	0	140	40	57	20,5	14,6
225	180	16	700 647 622	0	120	40	48	20,5	16,4
225	200	16	700 647 623	0	100	40	40	20,5	18,2
250	180	16	700 647 624	0	150	40	54	22,7	16,4
250	200	16	700 647 625	0	130	40	55	22,7	18,2
250	225	16	700 647 626	0	110	40	40	22,7	20,5
280	200	16	700 647 627	0	160	40	58	25,4	18,2
280	225	16	700 647 628	0	130	40	52	25,4	20,5
280	250	16	700 647 629	0	110	40	47	25,4	22,7
315	225	16	700 647 630	0	160	40	62	28,6	20,5
315	250	16	700 647 631	0	140	40	57	28,6	22,7
315	280	16	700 647 632	0	120	40	54	28,6	25,4
355	250	16	700 647 633	0	180	40	74	32,2	22,7
355	250	16	700 647 634	0	150	40	61	32,2	25,4
355	315	16	700 647 635	0	120	40	51	32,2	28,6
400	280	16	700 647 636	0	200	40	85	36,3	25,4
400	315	16	700 647 637	0	170	40	75	36,3	28,6
400	355	16	700 647 638	0	130	40	58	36,3	32,2
450	315	16	700 647 639	0	210	40	86	40,9	28,6
450	355	16	700 647 640	0	180	40	79	40,9	32,2
450	400	16	700 647 641	0	140	40	65	40,9	36,3
500	315	16	700 647 642	0	260	40	107	45,4	28,6
500	355	16	700 647 643	0	220	40	91	45,4	32,2
500	400	16	700 647 644	0	190	40	86	45,4	36,3
500	450	16	700 647 645	0	140	40	65	45,4	40,9
560	450	16	700 647 646	0	200	40	91	50,8	40,9
560	500	16	700 647 647	0	150	40	70	50,8	45,4
630	500	16	700 647 648	0	220	40	99	57,2	45,4
630	560	16	700 647 649	0	170	40	84	57,2	50,8

Data sheet

valid from: 9/19/17



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>