




Water jet suction pump type P20 PVC-U


- DN 10-20: BSP parallel female thread and solvent cement socked metric with EPDM o-rings
- DN 25-50: Solvent cement socket metric with EPDM o-rings
- DN 65-80: Solvent cement spigot metric without o-rings

d	DN	Size	PN	Code	SP	Weight
(mm)	(mm)	(inch)	(bar)			(kg)
16	10	¾	10	199 041 120		0.138
20	15	½	10	199 041 121		0.228
25	20	¾	10	199 041 122	1	0.363
32	25	1	10	199 041 123		0.468
40	32	1 ¼	10	199 041 124		0.841
50	40	1 ½	10	199 041 125		1.360
63	50	2	10	199 041 126	1	2.440
75	65	2 ½	10	199 041 127		2.313
90	80	3	10	199 041 128	1	4.090


d	H	H1	L	L1	L2	closest	G1	G
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	inch	(inch)	(inch)
						(inch)		
16		35		110	40	¾	¾	R 3/4
20		35		125	40	½	¾	R 1
25		45		145	45	¾	¾	R 1 1/4
32	96	71	245	195		1	1 ½	R 1 1/2
40	116	87	297	239		1 ¼	2	R 2
50	139	105	369	301		1 ½	2 ¼	R 2 1/4
63	169	128	433	351		2	2 ¾	R 2 3/4
75		115	388			2 ½		
90		149	465			3		



DN 10 - 20



DN 25 - 50



DN 65 - 80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>