


Transition elbow 90° PE/brass (Ms 58) Male thread



- PE10 **SDR16**, metric
- With integral pipe fixation
- 4mm pin connectors
- Limited path fusion indicators
- Supplied as a kit



d	Thread Type	Size	DN	PN	Code	weight	Do	L1	P1	SLW	SDR pipe
(mm)		(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	
20	R	½	15	16	720 100 756	0.240	31	96	32	30	9-11
25	R	¾	20	16	720 100 757	0.260	36	97	32	35	9-11
32	R	1	25	16	720 100 758	0.368	44	98	34	40	9-11
32	R	1 ¼	25	16	720 100 766	0.500	44	100	34	50	9-11
32	R	1 ½	25	16	720 100 767	0.562	44	100	34	60	9-11
40	R	1	32	16	720 100 771	0.511	54	107	38	50	9-11
40	R	1 ¼	32	16	720 100 759	0.534	54	109	38	50	9-11
40	R	1 ½	32	16	720 100 772	0.615	54	109	38	60	9-11
50	R	1	40	16	720 100 776	0.677	66	116	42	60	9-11
50	R	1 ¼	40	16	720 100 777	0.771	66	118	42	60	9-11
50	R	1 ½	40	16	720 100 760	0.734	66	118	42	60	9-11
63	R	1 ¼	50	16	720 100 782	1.040	81	128	46	70	9-17.6
63	R	1 ½	50	16	720 100 783	1.039	81	128	46	70	9-17.6
63	R	2	50	16	720 100 761	1.108	81	132	46	70	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>