




Tapping saddle With 360° rotatable outlet


- 10 bar Gas / 16 bar Water
- With integrated cutter to tap live mains under pressure
- **Suitable to tap SDR11 pipes**
- 4mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- O-ring-sealed screw cap

* Topload: delivery without lower part for assembling as Topload with tool no. 799.350.477; angleadaptor (799.350.340) for fusion cable required



#	d (mm)	Do3 (mm)	DN (mm)	PN (bar)	Code	Weight (kg)
	315	63	300	16	193 131 868	1.473
*	355	63	350	16	193 131 867	1.473
*	400	63	400	16	193 131 877	1.473

L (mm)	L4 (mm)	Db (mm)	W (mm)	H (mm)	H4 (mm)	SDR pipe
160	100	33	164	328	206	11 - 33
160	100	33	165	328	206	11 - 33
160	100	33	165	328	206	11 - 33



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>