





Diaphragm valve type 514 PVC-C With solvent cement sockets ASTM

Model:

- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Handwheel with built-in locking mechanism
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve (see diagram)
- Self adjusting multifunctional module with integrated limit switches

* O-Ring material: FKM

d	DN	Size	PN	kv-value	EPDM	SP	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)
				(L/min)			
20	15	½	10	125	163 514 612	1	0.310
25	20	¾	10	271	163 514 613	1	0.445
32	25	1	10	481	163 514 614	1	0.708
40	32	1 ¼	10	759	163 514 615	1	0.998
50	40	1 ½	10	1263	163 514 616	1	1.692
63	50	2	10	1728	163 514 617	1	2.583

FKM	PTFE/EPDM	SP	Weight
Code	Code		(kg)
163 514 662	163 514 632	1	0.310
163 514 663	163 514 633	1	0.522
163 514 664	163 514 634	1	0.727
163 514 665	163 514 635	1	1.412
163 514 666	163 514 636	1	1.726
163 514 667	163 514 637	1	3.382

D	D2	D3	H	H1	H2	L	L2	M	z	Lift =
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	Hx
										(mm)
65	65	43	73	14	12	141	25	M6	96	7
80	65	51	81	18	12	165	25	M6	114	10
88	87	58	107	22	12	179	25	M6	122	13
101	87	72	115	26	15	204	45	M8	140	15
117	135	83	148	32	15	230	45	M8	160	19
144	135	100	166	39	15	268	45	M8	190	25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>