




## Tee 90° ridotto PE100 SDR17/17,6

### Model:

- 10 bar gas / 16 bar acqua
- Fittings are injection moulded



d (mm)	d2 (mm)	DN (mm)	PN	code	NPK	weight (kg)	L2 (mm)	Lmax (mm)	Q1 (mm)	Q2 (mm)	s1 (mm)	s2 (mm)
90	50	80	10	753 201 827	423 216	0.630	117	275	79	55	5.4	3.0
90	63	80	10	753 200 829	423 236	0.560	123	275	79	63	5.4	3.8
90	75	80	10	753 201 855		0.580	132	286	80	75	5.4	4.5
110	63	100	10	753 200 828	423 237	1.010	147	318	82	63	6.6	3.8
110	75	100	10	753 200 131		1.029	155	324	85	74	6.6	4.5
110	90	100	10	753 200 832	423 277	0.941	158	318	82	79	6.6	5.4
125	90	100	10	753 200 132		1.500	165	354	90	82	7.4	5.4
125	110	100	10	753 200 133		1.560	167	354	90	85	7.4	6.6
160	63	150	10	753 200 834	423 242	2.554	130	330	86	63	9.5	3.8
160	75	150	10	753 200 880		1.920	180	420	105	75	9.5	4.5
160	90	150	10	753 200 836	423 282	1.972	188	410	98	79	9.5	5.4
160	110	150	10	753 200 837	423 322	2.716	195	410	98	82	9.5	6.6
180	90	150	10	753 200 881		2.780	200	484	110	82	10.7	5.4
180	110	150	10	753 200 150		4.320	205	486	110	86	10.7	6.6
180	160	150	10	753 200 882		5.560	220	484	110	100	18.7	9.5
200	63	200	10	753 201 873	423 244	6.800	190	500	122	63	11.9	3.8
200	90	200	10	753 201 874	423 284	6.900	207	500	122	79	11.9	5.4
200	110	200	10	753 201 875	423 324	5.097	215	500	122	82	11.9	6.6
200	160	200	10	753 201 876	423 374	7.400	234	500	122	98	11.9	9.5
225	75	200	10	753 200 839	423 265	7.128	277	555	120	70	13.4	4.5
225	90	200	10	753 200 840	423 285	4.732	226	555	127	80	13.4	5.4
225	110	200	10	753 200 841	423 325	4.700	235	555	127	82	13.4	6.6
225	160	200	10	753 200 842	423 374	5.922	253	555	127	98	13.4	9.5
225	180	200	10	753 200 843	423 425	7.211	280	550	120	105	13.4	10.7
250	110	250	10	753 201 878	423 326	8.185	242	575	130	82	14.8	6.6
250	160	250	10	753 201 879	423 376	9.800	261	575	130	98	14.8	9.5
315	110	300	10	753 200 851	423 328	15.621	277	695	150	82	18.7	6.6
315	160	300	10	753 200 852	423 378	12.200	296	695	150	102	18.7	9.5
315	200	300	10	753 200 152		17.910	313	690	155	117	18.7	11.9
315	225	300	10	753 200 153		16.035	320	690	155	125	18.7	13.4
315	250	300	10	753 200 854		15.500	325	695	150	130	18.7	14.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>