



Joint torique pour unions EPDM/FKM

Exécution:

- Pour ecoFIT, PROGEF Std/Plus, SYGEF Std unions et union d'adaptation pour soudage bout à bout
- Dureté: env. 65° Shore
- EPDM température minimale -40°C
- FKM température minimum -15°C

Remarque:

For the O-Rings of new unions as of 10/2022, see respective union datasheet

d (mm)	DN (mm)	EPDM Code	CAN	Poids (kg)	FKM Code	CAN	CAN	D (mm)	D1 (mm)	D2 (mm)
20	15	748 410 006		0.002	749 410 006			27.28	20.22	3.53
25	20	748 410 007		0.002	749 410 007			35.23	28.17	3.53
32	25	748 410 008		0.003	749 410 008			39.99	32.93	3.53
40	32	748 410 009		0.003	749 410 009			51.33	40.65	5.34
50	40	748 410 010		0.004	749 410 010			57.68	46.99	5.34
63	50	748 410 011		0.005	749 410 011			70.37	56.69	5.34
75 / 90	65 / 80	748 410 383		0.006	749 410 383			85.31	74.63	5.34
110	110	748 410 384		0.016	749 410 384			128.68	114.70	6.99

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>