

Løsflenser PP-Stål

Modell


- Material: PP (30% glassfiber forsterket) med stålring
- Metrisk: ISO 7005, EN 1092, ISO 9624
- ASME: ANSI/ASME B 16.5 class 150, ASTM D2024, BS 1560, BS EN 1759
- Spesialkrave ANSI for d25 - d50 og d90 er påkrevet

AL: Antall hull

* FM 1613 godkjent - 15 bar


** Profilert løsflens

d	Størrelse	DN	D	PN	Standard	Bolt circle	Design
(mm)	(inch)	(mm)	(mm)	(bar)			
20	¾	15	95	16	ASME	class 150	Butt/Muffe
20		15	95	16	Metrisk	PN10	Butt/Muffe
25		20	105	16	Metrisk	PN10	Butt/Muffe
25	¾	20	105	16	ASME	class 150	Butt/Muffe
32		25	115	16	Metrisk	PN10	Butt/Muffe
32	1	25	115	16	ASME	class 150	Butt/Muffe
40		32	140	16	Metrisk	PN10	Butt/Muffe
40	1 ¼	32	140	16	ASME	class 150	Butt/Muffe
50		40	150	16	Metrisk	PN10	Butt/Muffe
50	1 ½	40	150	16	ASME	class 150	Butt/Muffe
63	2	50	165	16	Metrisk	PN10	Butt/Muffe
63		50	165	16	ASME	class 150	Butt/Muffe
75		65	185	16	Metrisk	PN10	Butt/Muffe
75	2 ½	65	185	16	ASME	class 150	Butt/Muffe
*		80	200	16	Metrisk	PN10	Butt
90		80	200	16	Metrisk	PN10	Muffe
90		80	200	16	Metrisk	PN10	Butt
90	3	80	200	16	ASME	class 150	Muffe
90	3	80	200	16	ASME	class 150	Butt
*		100	223	16	Metrisk	PN10	Butt
110		100	220	16	Metrisk	PN10	Muffe
110		100	220	16	Metrisk	PN10	Butt
110	4	100	229	16	ASME	class 150	Muffe
110	4	100	229	16	ASME	class 150	Butt
*		100	223	16	Metrisk	PN10	Butt
125		100	220	16	Metrisk	PN10	Butt
125		125	250	16	Metrisk	PN10	Muffe
*		125	250	16	Metrisk	PN10	Butt
140		125	250	16	Metrisk	PN10	Butt
140		125	250	16	Metrisk	PN10	Muffe
*		150	285	16	Metrisk	PN10	Butt
160	6	150	285	16	Metrisk/ASME	PN10/ class 150	Butt
160	6	150	285	16	Metrisk/ASME	PN10/ class 150	Muffe
*		150	285	16	Metrisk	PN10	Butt
180		150	285	16	Metrisk	PN10/ Class 150	Butt
*, **		200	344	16	Metrisk	PN16	Butt
200	8	200	340	16	Metrisk/ASME	PN10/ class 150	Butt
200	8	200	340	16	Metrisk/ASME	PN10/ class 150	Muffe
*, **		200	344	16	Metrisk	PN16	Butt
225	8	200	340	16	Metrisk/ASME	PN10/ class 150	Butt
225	8	200	340	16	Metrisk/ASME	PN10/ class 150	Muffe
*, **		250	410	16	Metrisk	PN16	Butt
250		225	395	16	Metrisk	PN10	Muffe
250	10	250	406	10	ASME	class 150	Butt



d	Størrelse	DN	D	PN	Standard	Bolt circle	Design
(mm)	(inch)	(mm)	(mm)	(bar)			
250		250	395	16	Metrisk	PN10	Butt
250		250	395	16	Metrisk	PN10	Muffe
*, **	280	250	410	16	Metrisk	PN16	Butt
	280	250	395	16	Metrisk	PN10	Butt
	280	250	395	16	Metrisk	PN10	Muffe
*, **	315	300	455	16	Metrisk	PN16	Butt
	315	300	445	16	Metrisk	PN10	Butt
	315	300	445	16	Metrisk	PN10	Muffe
	315	12	300	483	10	ASME	class 150
*, **	355	350	521	16	Metrisk	PN16	Butt
	355	350	515	16	Metrisk	PN10	Butt
	355	350	515	16	Metrisk	PN10	Muffe
	355	14	350	540	10	ASME	class 150
*, **	400	400	582	16	Metrisk	PN16	Butt
	400	400	574	16	Metrisk	PN10	Butt
	400	400	574	16	Metrisk	PN10	Muffe
	400	16	400	597	10	ASME	class 150
*, **	450	500	685	10	Metrisk	PN10	Butt
*, **	500	500	685	10	Metrisk	PN10	Butt
**	560	600	796	10	Metrisk	PN10	Butt
**	630	600	800	10	Metrisk	PN10	Butt
**	710	700	912	6	Metrisk	PN10	Butt
**	800	800	1026	6	Metrisk	PN10	Butt
**	900	900	1129	6	Metrisk	PN10	Butt
	450	20	500	712	10	ASME	class 150

d	Kode	NRF	Vekt	D1	D2	D3	H maks.	AL	SC
(mm)			(kg)	(mm)	(mm)	(mm)	(mm)		
20	727 701 206		0,213	60	28	16	12	4	M12
	727 700 206	222 82 53	0,216	65	28	14	12	4	M12
25	727 700 207	222 82 54	0,279	75	34	14	12	4	M12
	727 701 207		0,260	70	34	16	12	4	M12
32	727 700 208	222 82 55	0,429	85	42	14	16	4	M12
	727 701 208		0,416	79	42	16	16	4	M12
40	727 700 209	222 82 56	0,621	100	51	18	16	4	M16
	727 701 209		0,730	89	51	16	16	4	M16
50	727 700 210	222 82 57	0,722	110	62	18	20	4	M16
	727 701 210		0,809	98	62	16	18	4	M16
63	727 700 211	222 82 58	0,900	125	78	18	20	4	M16
	727 701 211		0,866	121	78	19	18	4	M16
75	727 700 212	222 82 59	1,110	145	92	18	20	4	M16
	727 701 212		1,117	140	92	19	18	4	M16
*	90 724 700 313		1,390	160	108	18	20	8	M16
	90 727 700 213	222 82 61	1,369	160	110	18	20	8	M16
	90 727 700 313	254 21 94	1,390	160	108	18	20	8	M16
	90 727 701 213		1,492	152	110	19	20	4	M16
	90 727 701 313		1,499	152	108	19	20	4	M16
*	110 724 700 314		1,407	180	128	18	20	8	M16
	110 727 700 214	222 82 62	1,522	180	133	18	20	8	M16
	110 727 700 314	254 21 95	1,407	180	128	18	20	8	M16
	110 727 701 214		1,695	190	133	19	20	8	M16
	110 727 701 314		1,739	190	128	19	20	8	M16
*	125 724 700 315		1,408	180	135	18	20	8	M16
	125 727 700 315	222 92 46	1,408	180	135	18	20	8	M16
	125 727 700 815	222 92 53	2,475	210	150	18	26	8	M16
*	140 724 700 316		2,318	210	158	18	24	8	M16
	140 727 700 716	222 92 47	2,318	210	158	18	24	8	M16
	140 727 700 816	222 92 54	2,033	210	167	18	26	8	M16
*	160 724 700 317		3,491	240	178	22	28	8	M20



	d	Kode	NRF	Vekt	D1	D2	D3	H maks.	AL	SC
	(mm)			(kg)	(mm)	(mm)	(mm)	(mm)		
	160	727 700 717	222 92 48	3,491	240	178	22	24	8	M20
	160	727 700 817	222 82 67	3,167	240	190	22	26	8	M20
*	180	724 700 318		3,108	240	188	22	28	8	M20
	180	727 700 718	222 92 49	3,108	240	188	22	24	8	M20
*, **	200	724 700 319	222 92 36	3,549	295	235	22	31	12	M20
	200	727 700 719	222 92 51	5,600	295	235	22	27	8	M20
	200	727 700 819	222 92 55	6,143	295	226	22	29	8	M20
*, **	225	724 700 320	222 92 37	3,380	295	238	22	31	12	M20
	225	727 700 720	222 92 52	5,533	297	238	22	27	8	M20
	225	727 700 820	222 92 56	4,448	297	250	22	29	8	M20
*, **	250	724 700 321	222 92 38	6,390	355	288	26	35	12	M24
	250	727 700 031	222 92 45	8,340	325	277	22	32	8	M20
	250	727 701 321		6,000	362	293	25	30	12	M24
	250	727 700 721	222 76 42	6,632	350	288	22	30	12	M20
	250	727 700 821		7,179	350	277	22	32	12	M20
*, **	280	724 700 322	222 92 39	6,310	355	294	26	36	12	M24
	280	727 700 722	222 76 43	6,573	350	294	22	30	12	M20
	280	727 700 822	222 92 58	5,547	350	310	22	32	12	M20
*, **	315	724 700 323	222 92 41	9,740	410	338	26	43	12	M24
	315	727 700 723	222 76 44	7,903	400	338	22	34	12	M20
	315	727 700 823	222 92 59	6,980	400	348	22	36	12	M20
	315	727 701 322		11,800	432	338	25	34	12	M24
*, **	355	724 700 324	222 92 42	15,203	470	376	26	55	16	M24
	355	727 700 724	222 76 45	14,587	460	376	23	40	16	M20
	355	727 700 824	222 92 61	12,465	460	388	23	42	16	M20
	355	727 701 323		17,900	476	376	29	42	12	M27
*, **	400	724 700 325		20,600	525	430	30	56	16	M27
	400	727 700 725	222 76 46	20,034	515	430	26	40	16	M24
	400	727 700 825	222 92 62	17,607	515	442	26	42	16	M24
	400	727 701 324		24,500	539	429	29	44	16	M27
*, **	450	724 700 426	222 76 47	25,600	620	517	26	56	20	M24
*, **	500	724 700 427	222 76 48	21,061	620	533	26	56	20	M24
**	560	724 700 428	222 76 49	35,000	725	618	30	68	20	M27
**	630	724 700 429	222 76 51	28,500	725	645	30	68	20	M27
**	710	724 700 430	222 76 52	25,500	840	740	30	49	24	M27
**	800	724 700 431	222 76 63	39,300	950	843	33	58	24	M30
**	900	724 700 432	222 76 64	48,500	1050	947	33	62	28	M30
	450	727 701 325		33,600	635	540	32	53	20	M30

De tekniske data er uforpliktende. De er hverken uttrykk for garanterte egenskaper, funksjoner eller for garantert holdbarhet. Rett til endringer forbeholdes. Våre generelle salgsbetingelser er gjeldene.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>