



SYGEF 标准型
243型凸耳式蝶阀 FO (常开)
无手动操作手柄

- 型号:**
- (阀体) 外壳材质 : PP-GF30 , SS316凸耳内嵌
 - 控制范围 : 90°<
 - 总长度符合EN 558, ISO 5752标准
 - 连接尺寸 : ISO7005 PN10 , EN1092 PN10 , DIN2501 PN10
- 选项:**
- 可选项 : 位置反馈及限位开关 (限位开关需要单独采购)

d	Size	DN	PN	kv-value	FKM	SP	weight
(mm)	(inch)	(mm)	(bar)	($\Delta p=1$ bar)	code		(kg)
				(l/min)			
63	2	50	10	740	199 243 482	1	3,499
75	2 1/2	65	10	1500	199 243 483	1	3,656
90	3	80	10	2400	199 243 484	1	4,692
110	4	100	10	3800	199 243 485	1	6,406
140	5	125	10	8600	199 243 486	1	9,222
160	6	150	10	11400	199 243 487	1	12,902
225	8	200	10	19900	199 243 488	1	16,691
280	10	250	10	34000	199 243 489	1	33,880
315	12	300	5	50000	199 243 490	1	43,985

d	Hmax	Lmax	Wmax	U	V	H4	V1	Lg	D2	Q1	Q2	d2	k
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	328,1	274,4	165,0	90	133,3	23	78,8	44,7	160	40		M16	125
75	341,0	274,4	182,0	90	139,9	23	85,1	45,7	180	54	35	M16	145
90	365,7	325,2	210,0	90	145,6	23	91,2	48,7	195	67	50	M16	160
110	388,3	359,6	240,0	90	166,0	23	107,5	55,6	226	88	74	M16	180
140	452,2	418,0	272,0	90	180,0	23	122,7	63,5	258	113	97	M16	210
160	476,6	434,0	280,0	90	189,0	23	134,5	71,5	284	139	123	M20	240
225	532,0	498,4	360,0	90	210,5	23	161,5	72,5	341	178	169	M20	295
280	679,5	646,0	440,0	125	264,4	23	206,9	113,2	412	210	207	M20	350
315	749,0	681,0	510,0	125	285,2	23	235,5	114,6	482	256	253	M20	400

d	Y	E	Y1	M2
(mm)	(mm)	(mm)	(mm)	(mm)
63	98,2	70,4	15,0	137,2
75	98,2	70,4	15,0	137,2
90	111,1	83,3	15,0	162,6
110	114,8	87,0		179,8
140	149,5	107,5		209,0
160	153,1	111,1		217,0
225	160,0	118,0		249,2
280	190,0	148,0	18,2	323,0
315	210,1	168,0	18,2	340,5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 2025/2/8



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>