



JRG LegioStop Unité compacte isolée PU

- Description: Pour le montage dans les systèmes de prémurs GEBERIT Duofix ou Viega/ Nussbaum Optivis-Tec.
- Matériau: Bronze, mousse polyuréthane
- Conductivité thermique: 0,037 W/mK selon la norme EN 12667
- Classe de matériaux de construction: E (selon EN 13501-1)
- Composé de: 2 joints de sortie, 2 unités d'obturation, unité compacte, 2 contre-connexions UPZ KOAX et drainage PE DN56

GN	DN	JRG CAN		GF CAN	SP	Poids
(inch)	(mm)	Code		Code		(kg)
¾	20	5459.175		355 566 491	1	5.700

GN	DN	b	b1	d1 Rp	d2 Rp	d6	h1	h2	h3	h4	h5	l	l1	l2	l3
(inch)	(mm)	(mm)	(mm)	(inch)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
¾	20	153	428	¾	½	56	130	110	97	71	22	368	350	130	100

GN	DN	l4	l5	l6	PN	z1	z3
(inch)	(mm)	(mm)	(mm)	(mm)	(bar)	(mm)	(mm)
¾	20	70	490	365	10	23	15

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>