



## ecoFIT Backing Ring Steel ANSI 150

### Model:

- Material: A36 steel hot dipped galvanized
- Connecting dimensions: ANSI/ASME B16.5 Class 150
- Pressure rating equal PN10

### Note:

Please call us for availability of other sizes and dimensions

d (mm)	Code	Weight (kg)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	T (mm)	NH	Bolt size
63	<b>P8101421063</b>	0.98	160	121	78	19	8	4	M16
75	<b>P8101421075</b>	1.22	180	140	92	19	8	4	M16
90	<b>P8101421090</b>	1.68	195	152	109	19	10	4	M16
110	<b>P8101421110</b>	2.13	225	191	128	19	10	8	M16
125	<b>P8101421125</b>	1.95	225	191	138	19	10	8	M16
140	<b>P8101421140</b>	3.16	255	216	158	23	13	8	M18
160	<b>P8101421160</b>	4.03	285	241	177	23	13	8	M18
180	<b>P8101421180</b>	3.44	285	241	195	23	13	8	M18
200	<b>P8101421200</b>	5.11	340	298	231	23	13	8	M18
225	<b>P8101421225</b>	4.66	340	298	242	23	13	8	M18
250	<b>P8101421250</b>	7.79	405	362	290	26	16	12	M22
280	<b>P8101421280</b>	7.15	405	362	300	26	16	12	M22
315	<b>P8101421315</b>	14.38	480	432	341	26	20	12	M22
355	<b>P8101421355</b>	19.76	530	476	372	29	22	12	M27

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>