



45° Reducing Wye, PN 10, Standard PP

Model:

- Pressure de-rated 50%

	Suitable for	Code	e1 (mm)	e2 (mm)	z1 (inch)	z3 (inch)	z2 (inch)	A (inch)
*	63 - 50 mm	157 445 100	5.8	4.6	8.90	11.06	6.42	5.91
*	75 - 50 mm	157 445 105	6.9	4.6	9.47	11.63	6.52	5.91
*	75 - 63 mm	157 445 106	6.9	5.8	9.47	11.63	6.52	5.91
*	90 - 63 mm	157 445 112	8.2	5.8	12.15	14.71	8.61	7.87
*	90 - 75 mm	157 445 113	8.2	6.9	12.15	14.71	8.61	7.87
*	110 - 63 mm	157 345 119	10.0	5.8	13.10	19.20	8.77	7.87
*	110 - 75 mm	157 445 120	10.0	6.9	13.10	16.25	8.77	7.87
*	110 - 90 mm	157 445 121	10.0	8.2	13.07	16.44	8.77	7.87
*	125 - 110 mm	157 445 129	11.4	10.0	13.81	17.36	8.89	7.87
*	140 - 110 mm	157 445 138	12.8	10.0	14.53	18.46	9.02	7.87
*	140 - 125 mm	157 445 139	12.8	11.4	14.53	18.46	9.02	7.87
*	160 - 90 mm	157 445 122	14.6	8.2	15.48	23.27	9.18	7.87
*	160 - 140 mm	157 445 150	14.6	12.8	15.48	19.80	9.18	7.87
*	160 - 110 mm	157 445 148	14.6	10.0	15.48	19.80	9.18	7.87
*	200 - 160 mm	157 445 160	18.2	14.6	19.35	24.65	11.47	9.84
*	225 - 110 mm	157 445 169	20.5	10.0	20.54	26.44	11.68	9.84
*	225 - 160 mm	157 445 170	20.5	14.6	20.54	26.44	11.68	9.84
*	225 - 200 mm	157 445 171	20.5	18.2	20.54	26.44	11.68	9.84
*	250 - 160 mm	157 445 181	22.8	14.6	23.69	30.98	13.85	11.81
*	250 - 225 mm	157 445 183	22.8	20.5	23.69	30.47	13.85	11.81
*	315 - 225 mm	157 445 208	28.7	20.5	28.75	33.48	16.35	13.78
*	315 - 250 mm	157 445 209	28.7	22.8	28.75	32.27	16.35	13.78

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>