



Analytical Threaded Sensor, PN 16 PVDF-HP

IR Plus/BCF Plus Fusion

d	FNPT	FM	SDR	Code	e	L	L1	L2
(mm)	(inch)				(mm)	(mm)	(mm)	(mm)
50	1/4	BCF, IR	21	735 991 840	3.0	135	58	77
50	1/2	BCF, IR	21	735 991 841	3.0	135	58	77
50	3/4	BCF, IR	21	735 991 842	3.0	135	58	77
50	1	BCF, IR	21	735 991 843	3.0	135	58	77
63	1/4	BCF, IR	21	735 991 844	3.0	151	66	85
63	1/2	BCF, IR	21	735 991 845	3.0	151	66	85
63	3/4	BCF, IR	21	735 991 846	3.0	151	66	85
63	1	BCF, IR	21	735 991 847	3.0	151	66	85
75	1/4	BCF, IR	21	735 991 848	3.6	165	75	90
75	1/2	BCF, IR	21	735 991 849	3.6	165	75	90
75	3/4	BCF, IR	21	735 991 850	3.6	165	75	90
75	1	BCF, IR	21	735 991 851	3.6	165	75	90
90	1/4	BCF, IR	21	735 991 852	4.3	188	90	98
90	1/2	BCF, IR	21	735 991 853	4.3	188	90	98
90	3/4	BCF, IR	21	735 991 854	4.3	188	90	98
90	1	BCF, IR	21	735 991 855	4.3	188	90	98
110	1/4	BCF, IR	21	735 991 856	5.3	219	110	109
110	1/2	BCF, IR	21	735 991 857	5.3	219	110	109
110	3/4	BCF, IR	21	735 991 858	5.3	219	110	109
110	1	BCF, IR	21	735 991 859	5.3	219	110	109

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>