






**PROGEF Plus silicone free
Butterfly valve type 567
Hand lever with ratchet settings**

Model:

- Material: PP-H / silicone free cleaned
- Up to DN 300: Overall length according to EN558 (DN 50-200: line 25, DN250, 300 line 16), ISO 5752
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI/ASME B 16.5 Class 150, BS 1560: 1989, BS 4504, JIS B 2220
- We recommend for the dimensions DN250 and DN300 only 6 bar maximum system pressure for the hand lever version

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d (mm)	Size (inch)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
63	2	50	10	740	167 567 402	1.277	167 567 422	0.969
75	2 ½	65	10	1500	167 567 403	1.056	167 567 423	1.270
90	3	80	10	2400	167 567 404	1.184	167 567 424	1.191
110	4	100	10	3800	167 567 405	1.737	167 567 425	1.751
140	5	125	10	8600	167 567 406	2.181	167 567 426	2.199
160	6	150	10	11400	167 567 407	2.966	167 567 427	2.989
225	8	200	10	19900	167 567 408	4.678	167 567 428	4.706
280	10	250	8	34000	167 567 409	11.841	167 567 429	11.841
315	12	300	8	50000	167 567 410	14.816	167 567 430	14.816

d (mm)	Hmax (mm)	Lmax (mm)	Wmax (mm)	H4 (mm)	V1 (mm)	Lg (mm)	d2 (mm)	Q1 (mm)	Q2 (mm)	Y (mm)	M1 (mm)	M2 (mm)
63	278.9	115.2	269.0	23	78.8	45	104	40		66.8	64.7	205.5
75	291.8	115.2	271.8	23	85.1	46	115	54	35	66.8	64.7	205.5
90	303.6	115.2	273.9	23	91.2	49	131	67	50	66.8	64.7	205.5
110	342.2	115.2	336.0	23	105.7	56	161	88	74	70.1	64.9	255.5
140	368.9	115.2	349.0	23	118.8	64	187	113	97	70.1	64.9	255.5
160	390.0	115.2	363.0	23	130.9	72	215	139	123	70.1	64.9	255.5
225	455.1	149.4	543.0	23	158.3	73	267	178	169	86.3	103.6	409.5
280	555.0	149.4	574.0	23	206.1	113	329	210	207	86.3	103.6	409.5
315	599.4	149.4	599.7	23	228.8	113	379	256	253	86.3	103.6	409.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>