



PROGEF Standard Tee 90° reduced SDR11/PN10

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR = Infrared welding compatible

¹with IR welded reducer

	d	d1	PN	FM	Code	Weight	L	L1	L2	L3	e	e1
	(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
	63	32	10	IR	727 208 351	0.161	65	70	25	25.0	5.8	2.9
	63	40	10	IR	727 208 350	0.165	65	70	25	25.0	5.8	3.7
	63	50	10	IR	727 208 352	0.170	65	70	25	25.0	5.8	4.6
	75	32	10	IR	727 208 353	0.238	70	75	25	25.0	6.8	2.9
	75	50	10	IR	727 208 354	0.249	70	75	25	25.0	6.8	4.6
	75	63	10	IR	727 208 355	0.258	70	75	25	25.0	6.8	5.8
	90	50	10	IR	727 208 357	0.420	80	85	25	25.0	8.2	4.6
	90	63	10	IR	727 208 358	0.428	80	85	25	25.0	8.2	5.8
	90	75	10	IR	727 208 359	0.430	80	85	25	25.0	8.2	6.8
	110	32	10	IR	727 208 360	0.652	90	95	30	25.0	10.0	2.9
	110	50	10	IR	727 208 361	0.659	90	95	30	25.0	10.0	4.6
	110	63	10	IR	727 208 362	0.665	90	95	30	25.0	10.0	5.8
	110	75	10	IR	727 208 363	0.681	90	95	30	25.0	10.0	6.8
	110	90	10	IR	727 208 364	0.701	90	95	30	25.0	10.0	8.2
1	125	63	10	IR	727 208 365	1.680	125	230	25	16.0	11.4	5.8
1	125	90	10	IR	727 208 066	1.700	125	225	25	40.0	11.4	8.2
1	125	110	10	IR	727 208 367	1.700	125	217	25	30.0	11.4	10.0
1	140	75	10	IR	727 208 068	2.400	140	245	28	41.0	12.7	6.8
1	140	90	10	IR	727 208 069	2.358	140	240	28	40.0	12.7	8.2
	160	63	10	IR	727 208 371	2.130	142	135	50	30.0	14.6	5.8
	160	75	10	IR	727 208 372	2.143	142	135	50	30.0	14.6	6.8
	160	90	10	IR	727 208 373	2.148	142	135	50	30.0	14.6	8.2
1	140	110	10	IR	727 208 370	2.380	140	242	28	33.0	12.7	10.0
	160	110	10	IR	727 208 374	2.186	142	135	50	30.0	14.6	10.0
	160	125	10	IR	727 208 075	3.600	160	272	28	32.0	14.6	11.4
1	200	160	10	IR	727 208 385	6.632	200	332	35	40.0	18.2	14.6
	200	180	10	IR	727 208 086	6.900	200	335	35	45.0	18.2	16.4
	225	90	10	IR	727 208 388	4.576	155	165	40	30.0	20.5	8.2
	225	110	10	IR	727 208 389	4.624	155	165	40	30.0	20.5	10.0
	225	160	10	IR	727 208 391	4.685	155	165	40	30.0	20.5	14.6
	250	160	10	IR	727 208 093	12.500	227	387	68	53.0	22.7	14.6
	90	32	10	IR	727 208 071	0.001	80	142	25	20.0	8.2	2.9
	180	63	10	IR	727 208 077	0.001	215	299	97	28.0	16.4	6.2
	180	110	10	IR	727 208 078	0.001	215	355	97	40.0	16.4	10.0
	315	160	10	IR	727 208 080	0.001	283	421	86	37.5	28.6	15.4
	63	25	10	IR	727 208 356	0.001	65	112	25	20.0	5.8	2.3
	63	25	10	IR	727 208 390	0.001	65	112	25	20.0	5.8	2.3
	90	32	10	IR	727 208 392	0.001	80	142	25	20.0	8.2	2.9
	180	110	10	IR	727 208 399	0.001	215	355	97	40.0	16.4	10.0
	315	110	10	IR	727 208 400	0.001	283	416	86	29.5	28.6	10.6
	315	110	10	IR	727 208 079	0.001	283	416	86	29.5	28.6	10.6
	315	225	10	IR	727 208 081	0.001	283	508	86	60.0	28.6	20.5
	315	250	10	IR	727 208 082	0.001	283	502	86	63.0	28.6	22.7
	180	63	10	IR	727 208 398	0.001	215	299	97	28.0	16.4	6.2
	315	160	10	IR	727 208 401	0.001	283	421	86	37.5	28.6	15.4
	315	225	10	IR	727 208 402	0.001	283	508	86	60.0	28.6	20.5
	315	250	10	IR	727 208 403	0.001	283	502	86	63.0	28.6	22.7

Data sheet

valid from: 5/8/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>