





Ball valve type 375 PVC-U
With threaded sockets Rp

Model:

- True double union safe block ball valve
- Ball seat PTFE
- Handle includes integrated tool for ball seat adjustment
- Very compact dimensions
- z-dimension, valve end and union nut are not compatible with type 546

Range of use:

- Basic industrial applications without automation



d	DN	Thread Type	Size	PN	kv-value	EPDM	SP	Weight
(mm)	(mm)		(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)
					(l/min)			
75	65	Rp	2 1/2	10	5000	161 375 528	1	2.132
90	80	Rp	3	10	7000	161 375 529	1	2.132
110	100	Rp	4	10	11000	161 375 530	1	5.793

FKM	SP	Weight	D	H	L	L1	L2	L3	z
Code		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
161 375 538	1	2.132	145	129	184	179	110	103	118
161 375 539	1	3.213	168	143	212	209	128	120	140
161 375 540	1	5.793	210	169	244	250	150	141	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: <http://www.gfps.com>