


Data sheet

valid from: 5/5/25



Tee 90° ABS metric / BS

- >d225 - maximum operating temperature: +40°C



d	Size	PN	Code	SP	Weight	D	L	z	closest
(mm)	(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	inch
									(inch)
20		16	729 200 106	10	0.015	25	27	11	½
25		16	729 200 107	10	0.025	31	33	14	¾
32		10	729 200 108	10	0.042	40	39	17	1
40		10	729 200 109	10	0.078	49	47	21	1 ¼
50		10	729 200 110	5	0.134	61	57	26	1 ½
63		10	729 200 111	5	0.255	76	72	34	2
* 75	2 ½	10	729 200 112	6	0.404	90	84	40	2 ½
90		10	729 200 113	4	0.664	107	98	47	3
110		10	729 200 114	6	1.010	133	116	55	4
* 140	5	10	729 200 116	1	2.570	169	147	71	5
160		10	729 200 117	4	3.752	193	167	81	6
200		10	729 200 119	1	4.446	225	207	101	8
225		10	729 200 120	1	6.860	256	233	114	8
	½	15	729 201 106	10	0.028	30	30	13	
	¾	15	729 201 107	10	0.039	35	37	16	
	1	15	729 201 108	10	0.061	43	43	19	
	1 ¼	15	729 201 109	10	0.075	53	51	22	
	1 ½	15	729 201 110	5	0.152	58	56	26	
	2	15	729 201 111	5	0.307	73	68	32	
	3	15	729 201 113	5	0.703	107	97	46	
	4	15	729 201 115	2	1.417	138	122	59	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>