




**PROGEF Standard Ball valve type 127**  
**24V**  
**With manual emergency override**  
**With fixed flanges PP-H ser. ISO**

**Model:**

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts

**Option:**

- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit



| d    | DN   | Size   | PN    | kv-value            | EPDM               | Weight |
|------|------|--------|-------|---------------------|--------------------|--------|
| (mm) | (mm) | (inch) | (bar) | ( $\Delta p=1$ bar) | Code               | (kg)   |
|      |      |        |       | (l/min)             |                    |        |
| 20   | 15   | ½      | 10    | 185                 | <b>199 127 783</b> | 2.300  |
| 25   | 20   | ¾      | 10    | 350                 | <b>199 127 784</b> | 2.500  |
| 32   | 25   | 1      | 10    | 700                 | <b>199 127 785</b> | 2.700  |
| 40   | 32   | 1 ¼    | 10    | 1000                | <b>199 127 786</b> | 2.496  |
| 50   | 40   | 1 ½    | 10    | 1600                | <b>199 127 787</b> | 3.700  |
| 63   | 50   | 2      | 10    | 3100                | <b>199 127 788</b> | 4.800  |

| d    | Actuator | b1   | B3   | D1   | DE1  | E    | G    | H    | H1   | H4   | k1   | L    | L1   | Lz   | M    |
|------|----------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| (mm) |          | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| 20   | EA15     | 12   | 25   | 95   | 50   | 122  | M6   | 197  | 27   | 12   | 56   | 120  | 33   | 28   | 161  |
| 25   | EA15     | 12   | 25   | 105  | 58   | 122  | M6   | 201  | 30   | 12   | 75   | 139  | 33   | 33   | 161  |
| 32   | EA15     | 14   | 25   | 115  | 68   | 122  | M6   | 207  | 36   | 12   | 85   | 150  | 33   | 36   | 161  |
| 40   | EA15     | 16   | 45   | 140  | 84   | 122  | M8   | 213  | 44   | 15   | 100  | 170  | 33   | 43   | 161  |
| 50   | EA15     | 16   | 45   | 150  | 97   | 122  | M8   | 219  | 51   | 15   | 110  | 189  | 33   | 45   | 161  |
| 63   | EA15     | 18   | 45   | 165  | 124  | 122  | M8   | 234  | 64   | 15   | 125  | 219  | 33   | 51   | 161  |

| d    | M1   | M2   |
|------|------|------|
| (mm) | (mm) | (mm) |
| 20   | 77   | 83   |
| 25   | 77   | 83   |
| 32   | 77   | 83   |
| 40   | 77   | 83   |
| 50   | 77   | 83   |
| 63   | 77   | 83   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>