



2270超声波液位变送器
连续测量，盲版，4-20 mA/HART

- 原理：非接触式超声波时差法
- 测量范围：0.2...4米，0.25...6米
- 传感器主体：PP或PVDF
- 输出：4-20mA，两线；HART协议
- 供电：12...36 V DC

Operating Range	连接方式	Process Connection Size	Communication Interface	Electrical connction	MFR#
0.35 - 8 m	Thread	BSP 2"	4-20 mA, HART	Terminal	2270-P-1B-8
0.35 - 8 m	Thread	BSP 2"	4-20 mA, HART	Terminal	2270-V-1B-8
0.35 - 8 m	Thread	NPT 2"	4-20 mA, HART	Terminal	2270-V-1N-8
0.2 - 4 m	Thread	BSP 2"	4-20 mA, HART	Terminal	2270-P-1B-4
0.25 - 6 m	Thread	BSP 2"	4-20 mA, HART	Terminal	2270-P-1B-6
0.2 - 4 m	Thread	BSP 1.5"	4-20 mA, HART	Terminal	2270-V-1B-4
0.25 - 6 m	Thread	BSP 2"	4-20 mA, HART	Terminal	2270-V-1B-6
0.35 - 8 m	Thread	NPT 2"	4-20 mA, HART	Terminal	2270-P-1N-8
0.2 - 4 m	Thread	NPT 1.5"	4-20 mA, HART	Terminal	2270-P-1N-4
0.25 - 6 m	Thread	NPT 2"	4-20 mA, HART	Terminal	2270-P-1N-6
0.2 - 4 m	Thread	NPT 1.5"	4-20 mA, HART	Terminal	2270-V-1N-4
0.25 - 6 m	Thread	NPT 2"	4-20 mA, HART	Terminal	2270-V-1N-6

Measuring range (m)	Sensor Type	code	PF weight (kg)
0,35 - 8,00	PP	159 300 111	3 86 375 010 0,790
0,35 - 8,00	PVDF	159 300 115	3 86 375 010 0,790
0,35 - 8,00	PVDF	159 300 117	3 86 375 010 0,790
0,20 - 4,00	PP	159 300 155	3 86 375 010 0,790
0,25 - 6,00	PP	159 300 156	3 86 375 010 0,790
0,20 - 4,00	PVDF	159 300 162	3 86 375 010 0,790
0,25 - 6,00	PVDF	159 300 163	3 86 375 010 1,040
0,35 - 8,00	PP	159 300 116	3 86 375 010 0,790
0,20 - 4,00	PP	159 300 169	3 86 375 010 0,790
0,25 - 6,00	PP	159 300 170	3 86 375 010 0,790
0,20 - 4,00	PVDF	159 300 176	3 86 375 010 0,790
0,25 - 6,00	PVDF	159 300 177	3 86 375 010 0,790

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com