



JRG Sanipex MT Rohr in Ringen isoliert PE-Xc Mehrschichtverbundrohr mit Dämmung

- Beschreibung: in Ringen mit Dämmung 0.035 W/mK
- Material: Metallverbundrohr PE-X/AL/PE-X

d (mm)	DN (mm)	JRG Code	NPK	GF Code	NPK	SP
12	8	4606.012		351 612 035	312 121	50000
16	12	4606.016		351 616 735	312 121	25000
20	15	4606.020		351 620 735	312 122	1
26	20	4606.026		351 626 735	312 123	16666
32	25	4606.032		351 632 735	312 124	1

d (mm)	DN (mm)	Gewicht (kg)	d1 (mm)	l (m)	s (mm)	s1 (mm)	kg/m
12	8	8.500	24	100	1.70	6	0.058
16	12	8.900	28	50	2.25	6	0.178
20	15	12.950	32	50	2.50	6	0.259
26	20	18.200	38	50	3.00	6	0.364
32	25	18.950	52	25	3.00	10	0.435

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>