



Data sheet

valid from: 7/22/24



Valve end 375 PVC-U Solvent cement socket ASTM

Size (inch)	PN (bar)	Code	Weight (kg)	D (mm)	D1 (mm)	L (mm)	L1 (mm)	z (mm)
3/8	16	161 375 427	0.013	35	26	23	5	4
1/2	16	161 375 428	0.013	35	29	25	5	2
3/4	16	161 375 429	0.020	43	35	28	5	2
1	16	161 375 430	0.029	51	43	31	6	2
1 1/4	16	161 375 431	0.042	60	53	34	6	2
1 1/2	16	161 375 432	0.071	72	62	38	7	3
2	16	161 375 433	0.117	89	76	41	7	3
2 1/2	10	161 375 434	0.194	114	90	48	8	3
3	10	161 375 435	0.288	133	106	57	10	8
4	10	161 375 436	0.456	165	130	66	12	5



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>