

## MSA 2 CF @ 115V - Automatic Electrofusion Unit with protocols retrieval



The MSA 2 CF electro fusion unit combines light weight and high efficiency, thanks to its power switching technology and furthermore provides fusion documentation in PDF. The unit is extremely fast and simple, like COOL-FIT installations, with three basic operations required to the operator: connect, scan, start the fusion. It is robust, safe and ergonomic.

All is meant to simplify the job: the barcode scanner, for long distance reading, the cooling system to joint in series, the icon system, to keep the interaction between user and machine intuitive. The entire welding process is controlled and regulated with energy output compensation depending on ambient temperature and the indication of cooling time.

The unit has 1000 protocols permanently stored in the internal memory. The user can copy the fusion reports in an USB stick to print them out in PDF format.

Scope of delivery includes: transport box, standard and long angle adapters (4.0 mm), operating instructions, START/STOP badge and USB memory stick with PC applications.

The unit is suitable for welding PE, PP, INSTAFLEX PB d125-225, Fuseald1 1/2"-12" and PPro-Seal 1/2"-3".

### Technical Data:

- Operating temperature: -20°C to +50°C
- Mains voltage: 90V - 135V AC
- Mains frequency: 40-70 Hz
- Fusion data input mode: bar code, manual
- Fusion voltage: 3.6-42 V
- Fusion current: 90 A (max)
- Suggested power generators: 3.5 kVA
- Fittings range: d20-d450 (inner diameter) COOL-FIT 2.0/4.0
- Protocols format: PDF and binary (compatible with mini Welding Book)
- USB Port: Type A
- Protection factor: Class 1 / IP 65
- Mains cable: 4 m / Fusion cable: 4 m
- Weight: ca 12.5 kg
- Display: Graphical LCD, adjustable contrast
- Languages support: all

Description	Code	Weight (kg)
Barcode scanner, transport case, mini Welding Book	<b>790 156 023</b>	13.000

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>